


# K-MV G 230 V, 50 - 60 HZ D

Normally closed, 230 V, 50 to 60 Hz, directly operated

**HANSA FLEX**

## Caractéristiques

|                                |  |
|--------------------------------|--|
| <b>Raccord électrique</b>      | For Pg 11P connector socket, acc. to DIN 4400              |
| <b>Indice de protection</b>    | IP65 (with connector socket fitted)                        |
| <b>Température de fluide</b>   | max. +90 °C with Perbunan-seal; max. +130 °C with FKM-Seal |
| <b>Boîtier, siège de vanne</b> | Stainless steel  |
| <b>Pièces internes</b>         | Stainless steel  |
| <b>Joint d'étanchéité</b>      | Perbunan (NBR) or FKM                                      |



## Remarque

Autres informations sur demande.

## Description

Available versions, Directly operated, Combined operation

## Article

| Désignation    | Filets | Pression de service max.<br>(bar) | VN  | Matériau étanche | A<br>(mm) | B<br>(mm) | Conception |
|----------------|--------|-----------------------------------|-----|------------------|-----------|-----------|------------|
| K- 07 30 22 46 | G 1/8  | 20                                | 2,4 | NBR              | 80,0      | 30,0      | 1          |
| K- 07 30 22 48 | G 1/8  | 20                                | 2,4 | FKM              | 80,0      | 30,0      | 1          |
| K- 07 30 22 47 | G 1/4  | 12                                | 4,0 | NBR              | 85,0      | 45,0      | 1          |
| K- 07 30 22 49 | G 1/4  | 12                                | 4,0 | FKM              | 85,0      | 45,0      | 1          |