K-SHV
Safety valves

HANSA-FLEX

Caractéristiques

Pression de service	see operating pressure
Température de service	-10 °C to +200 °C
Joints	FKM
Ressort de pression	C steel
Boîtier	Brass





Remarque

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Autres informations sur demande.

Description

For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam. These valves are TÜV approved and have a TÜV type test number.

Informations supplémentaires

Important information: These valves are type-tested and are only allowed to be delivered with a fixed setting.

Article

Désignation	Filets	Pression de réponse	a (mm)	do (mm)	H (mm)	SW (mm)
K- 07 30 25 53	G 1/2"	0.2 bar	14,0	12,0	93,0	27
K- 07 30 25 54	G 1/2"	0.3 bar	14,0	12,0	93,0	27
K- 07 30 25 55	G 1/2"	0.4 bar	14,0	12,0	93,0	27
K- 07 30 25 56	G 1/2"	0.45 bar	14,0	12,0	93,0	27
K- 07 30 25 57	G 1/2"	0.5 bar	14,0	12,0	93,0	27
K- 07 30 25 58	G 1/2"	0.55 bar	14,0	12,0	93,0	27
K- 07 30 25 59	G 1/2"	0.6 bar	14,0	12,0	93,0	27
K- 07 30 25 60	G 1/2"	0.7 bar	14,0	12,0	93,0	27
K- 07 30 25 61	G 1/2"	0.8 bar	14,0	12,0	93,0	27
K- 07 30 25 62	G 1/2"	0.9 bar	14,0	12,0	93,0	27
K- 07 30 25 63	G 1/2"	1.0 bar	14,0	12,0	93,0	27
K- 07 30 25 64	G 1/2"	1.1 bar	14,0	12,0	93,0	27
K- 07 30 25 65	G 1/2"	1.2 bar	14,0	12,0	93,0	27
K- 07 30 25 66	G 1/2"	1.5 bar	14,0	12,0	93,0	27
K- 07 30 25 83	G 1/2"	2.0 bar	14,0	12,0	93,0	27
K- 07 30 25 84	G 1/2"	2.2 bar	14,0	12,0	93,0	27
K- 07 30 25 85	G 1/2"	2.4 bar	14,0	12,0	93,0	27
K- 07 30 25 86	G 1/2"	2.5 bar	14,0	12,0	93,0	27
K- 07 30 25 87	G 1/2"	2.6 bar	14,0	12,0	93,0	27
K- 07 30 25 93	G 1/2"	3.0 bar	14,0	12,0	93,0	27
K- 07 30 25 94	G 1/2"	3.5 bar	14,0	12,0	93,0	27
K- 07 30 25 95	G 1/2"	3.8 bar	14,0	12,0	93,0	27
K- 07 30 25 96	G 1/2"	4.0 bar	14,0	12,0	93,0	27
K- 07 30 25 97	G 1/2"	4.1 bar	14,0	12,0	93,0	27
K- 07 30 25 98	G 1/2"	4.3 bar	14,0	12,0	93,0	27
K- 07 30 25 99	G 1/2"	4.5 bar	14,0	12,0	93,0	27
K- 07 30 26 00	G 1/2"	5.0 bar	14,0	12,0	93,0	27
K- 07 30 26 01	G 1/2"	5.5 bar	14,0	12,0	93,0	27
K- 07 30 26 02	G 1/2"	5.8 bar	14,0	12,0	93,0	27
K- 07 30 26 03	G 1/2"	6.0 bar	14,0	12,0	93,0	27
K- 07 30 26 04	G 1/2"	6.3 bar	14,0	12,0	93,0	27
K- 07 30 26 05	G 1/2"	6.5 bar	14,0	12,0	93,0	27
K- 07 30 26 06	G 1/2"	6.8 bar	14,0	12,0	93,0	27
K- 07 30 26 07	G 1/2"	7.0 bar	14,0	12,0	93,0	27
K- 07 30 26 08	G 1/2"	7.7 bar	14,0	12,0	93,0	27
K- 07 30 26 09	G 1/2"	7.8 bar	14,0	12,0	93,0	27

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.

Article

Désignation	Filets	Pression de réponse	a (mm)	do (mm)	H (mm)	SW (mm)
K- 07 30 26 10	G 1/2"	8.0 bar	14,0	12,0	93,0	27
K- 07 30 26 11	G 1/2"	8.5 bar	14,0	12,0	93,0	27
K- 07 30 26 12	G 1/2"	9.0 bar	14,0	12,0	93,0	27
K- 07 30 26 13	G 1/2"	9.5 bar	14,0	12,0	93,0	27
K- 07 30 25 67	G 1/2"	10.0 bar	14,0	12,0	93,0	27
K- 07 30 25 68	G 1/2"	10.5 bar	14,0	12,0	93,0	27
K- 07 30 25 69	G 1/2"	11.0 bar	14,0	12,0	93,0	27
K- 07 30 25 70	G 1/2"	11.5 bar	14,0	12,0	93,0	27
K- 07 30 25 71	G 1/2"	12.0 bar	14,0	12,0	93,0	27
K- 07 30 25 72	G 1/2"	12.5 bar	14,0	12,0	93,0	27
K- 07 30 25 73	G 1/2"	13.0 bar	14,0	12,0	93,0	27
K- 07 30 25 74	G 1/2"	14.0 bar	14,0	12,0	93,0	27
K- 07 30 25 75	G 1/2"	14.5 bar	14,0	12,0	93,0	27
K- 07 30 25 76	G 1/2"	15.0 bar	14,0	12,0	93,0	27
K- 07 30 25 77	G 1/2"	15.5 bar	14,0	12,0	93,0	27
K- 07 30 25 78	G 1/2"	16.0 bar	14,0	12,0	93,0	27
K- 07 30 25 79	G 1/2"	17.0 bar	14,0	12,0	93,0	27
K- 07 30 25 80	G 1/2"	17.5 bar	14,0	12,0	93,0	27
K- 07 30 25 81	G 1/2"	18.0 bar	14,0	12,0	93,0	27
K- 07 30 25 82	G 1/2"	18.5 bar	14,0	12,0	93,0	27
K- 07 30 25 88	G 1/2"	20.0 bar	14,0	12,0	93,0	27
K- 07 30 25 89	G 1/2"	22.0 bar	14,0	12,0	93,0	27
K- 07 30 25 90	G 1/2"	23.0 bar	14,0	12,0	93,0	27
K- 07 30 25 91	G 1/2"	24.0 bar	14,0	12,0	93,0	27
K- 07 30 25 92	G 1/2"	25.0 bar	14,0	12,0	93,0	27
K- 07 30 26 14	G 3/4"	0.2 bar	16,0	15,0	110,0	32
K- 07 30 26 15	G 3/4"	0.27 bar	16,0	15,0	110,0	32
K- 07 30 26 16	G 3/4"	0.5 bar	16,0	15,0	110,0	32
K- 07 30 26 17	G 3/4"	0.7 bar	16,0	15,0	110,0	32
K- 07 30 26 18	G 3/4"	0.8 bar	16,0	15,0	110,0	32
K- 07 30 26 19	G 3/4"	0.9 bar	16,0	15,0	110,0	32
K- 07 30 26 20	G 3/4"	1.0 bar	16,0	15,0	110,0	32
K- 07 30 26 21	G 3/4"	1.1 bar	16,0	15,0	110,0	32
K- 07 30 26 22	G 3/4"	1.5 bar	16,0	15,0	110,0	32
K- 07 30 26 23	G 3/4"	1.8 bar	16,0	15,0	110,0	32
K- 07 30 26 38	G 3/4"	2.0 bar	16,0	15,0	110,0	32
K- 07 30 26 39	G 3/4"	2.3 bar	16,0	15,0	110,0	32
K- 07 30 26 40	G 3/4"	2.5 bar	16,0	15,0	110,0	32
K- 07 30 26 41	G 3/4"	2.7 bar	16,0	15,0	110,0	32
K- 07 30 26 44	G 3/4"	3.0 bar	16,0	15,0	110,0	32
K- 07 30 26 45	G 3/4"	3.5 bar	16,0	15,0	110,0	32
K- 07 30 26 46	G 3/4"	4.0 bar	16,0	15,0	110,0	32
K- 07 30 26 47	G 3/4"	4.5 bar	16,0	15,0	110,0	32
K- 07 30 26 48	G 3/4"	5.0 bar	16,0	15,0	110,0	32
K- 07 30 26 49	G 3/4"	5.5 bar	16,0	15,0	110,0	32
K- 07 30 26 50	G 3/4"	6.0 bar	16,0	15,0	110,0	32
K- 07 30 26 51	G 3/4"	6.5 bar	16,0	15,0	110,0	32
K- 07 30 26 52	G 3/4"	6.7 bar	16,0	15,0	110,0	32
K- 07 30 26 53	G 3/4"	7.0 bar	16,0	15,0	110,0	32
K- 07 30 26 54	G 3/4"	7.5 bar	16,0	15,0	110,0	32
K- 07 30 26 55	G 3/4"	8.0 bar	16,0	15,0	110,0	32
K- 07 30 26 56	G 3/4"	8.5 bar	16,0	15,0	110,0	32
K- 07 30 26 57	G 3/4"	8.8 bar	16,0	15,0	110,0	32
K- 07 30 26 58	G 3/4"	9.0 bar	16,0	15,0	110,0	32
K- 07 30 26 59	G 3/4"	9.3 bar	16,0	15,0	110,0	32
K- 07 30 26 60	G 3/4"	9.5 bar	16,0	15,0	110,0	32
K- 07 30 26 24	G 3/4"	10.0 bar	16,0	15,0	110,0	32
K- 07 30 26 25	G 3/4"	10.5 bar	16,0	15,0	110,0	32
K- 07 30 26 26	G 3/4"	11.0 bar	16,0	15,0	110,0	32
K- 07 30 26 27	G 3/4"	11.5 bar	16,0	15,0	110,0	32
K- 07 30 26 28	G 3/4"	12.0 bar	16,0	15,0	110,0	32
K- 07 30 26 29	G 3/4"	13.0 bar	16,0	15,0	110,0	32
K- 07 30 26 30	G 3/4"	13.5 bar	16,0	15,0	110,0	32

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.

Article

Désignation	Filets	Pression de réponse	a (mm)	do (mm)	H (mm)	SW (mm)
K- 07 30 26 31	G 3/4"	14.0 bar	16,0	15,0	110,0	32
K- 07 30 26 32	G 3/4"	14.5 bar	16,0	15,0	110,0	32
K- 07 30 26 33	G 3/4"	15.0 bar	16,0	15,0	110,0	32
K- 07 30 26 34	G 3/4"	16.0 bar	16,0	15,0	110,0	32
K- 07 30 26 35	G 3/4"	16.5 bar	16,0	15,0	110,0	32
K- 07 30 26 36	G 3/4"	18.0 bar	16,0	15,0	110,0	32
K- 07 30 26 37	G 3/4"	18.5 bar	16,0	15,0	110,0	32
K- 07 30 26 42	G 3/4"	20.0 bar	16,0	15,0	110,0	32
K- 07 30 26 43	G 3/4"	21.0 bar	16,0	15,0	110,0	32
K- 07 30 26 61	G 1"	0.2 bar	18,0	20,0	132,0	41
K- 07 30 26 62	G 1"	0.3 bar	18,0	20,0	132,0	41
K- 07 30 26 63	G 1"	0.4 bar	18,0	20,0	132,0	41
K- 07 30 26 64	G 1"	0.5 bar	18,0	20,0	132,0	41
K- 07 30 26 65	G 1"	0.6 bar	18,0	20,0	132,0	41
K- 07 30 26 66	G 1"	0.7 bar	18,0	20,0	132,0	41
K- 07 30 26 67	G 1"	0.8 bar	18,0	20,0	132,0	41
K- 07 30 26 68	G 1"	0.9 bar	18,0	20,0	132,0	41
K- 07 30 26 69	G 1"	1.0 bar	18,0	20,0	132,0	41
K- 07 30 26 70	G 1"	1.2 bar	18,0	20,0	132,0	41
K- 07 30 26 71	G 1"	1.3 bar	18,0	20,0	132,0	41
K- 07 30 26 72	G 1"	1.5 bar	18,0	20,0	132,0	41
K- 07 30 26 73	G 1"	1.6 bar	18,0	20,0	132,0	41
K- 07 30 26 74	G 1"	1.7 bar	18,0	20,0	132,0	41
K- 07 30 26 75	G 1"	1.8 bar	18,0	20,0	132,0	41
K- 07 30 26 76	G 1"	1.9 bar	18,0	20,0	132,0	41
K- 07 30 26 92	G 1"	2.0 bar	18,0	20,0	132,0	41
K- 07 30 26 93	G 1"	2.3 bar	18,0	20,0	132,0	41
K- 07 30 26 94	G 1"	2.5 bar	18,0	20,0	132,0	41
K- 07 30 26 95	G 1"	2.9 bar	18,0	20,0	132,0	41
K- 07 30 26 99	G 1"	3.0 bar	18,0	20,0	132,0	41
K- 07 30 27 00	G 1"	3.3 bar	18,0	20,0	132,0	41
K- 07 30 27 01	G 1"	3.5 bar	18,0	20,0	132,0	41
K- 07 30 27 02	G 1"	3.9 bar	18,0	20,0	132,0	41
K- 07 30 27 03	G 1"	4.0 bar	18,0	20,0	132,0	41
K- 07 30 27 04	G 1"	4.5 bar	18,0	20,0	132,0	41
K- 07 30 27 05	G 1"	5.0 bar	18,0	20,0	132,0	41
K- 07 30 27 06	G 1"	5.3 bar	18,0	20,0	132,0	41
K- 07 30 27 07	G 1"	5.5 bar	18,0	20,0	132,0	41
K- 07 30 27 08	G 1"	6.0 bar	18,0	20,0	132,0	41
K- 07 30 27 09	G 1"	6.5 bar	18,0	20,0	132,0	41
K- 07 30 27 10	G 1"	6.6 bar	18,0	20,0	132,0	41
K- 07 30 27 11	G 1"	7.0 bar	18,0	20,0	132,0	41
K- 07 30 27 12	G 1"	7.3 bar	18,0	20,0	132,0	41
K- 07 30 27 13	G 1"	7.5 bar	18,0	20,0	132,0	41
K- 07 30 27 14	G 1"	7.7 bar	18,0	20,0	132,0	41
K- 07 30 27 15	G 1"	7.8 bar	18,0	20,0	132,0	41
K- 07 30 27 16	G 1"	8.0 bar	18,0	20,0	132,0	41
K- 07 30 27 17	G 1"	8.5 bar	18,0	20,0	132,0	41
K- 07 30 27 18	G 1"	8.9 bar	18,0	20,0	132,0	41
K- 07 30 27 19	G 1"	9.0 bar	18,0	20,0	132,0	41
K- 07 30 27 20	G 1"	9.3 bar	18,0	20,0	132,0	41
K- 07 30 27 21	G 1"	9.5 bar	18,0	20,0	132,0	41
K- 07 30 26 77	G 1"	10.0 bar	18,0	20,0	132,0	41
K- 07 30 26 78	G 1"	10.5 bar	18,0	20,0	132,0	41
K- 07 30 26 79	G 1"	11.0 bar	18,0	20,0	132,0	41
K- 07 30 26 80	G 1"	11.7 bar	18,0	20,0	132,0	41
K- 07 30 26 81	G 1"	12.0 bar	18,0	20,0	132,0	41
K- 07 30 26 82	G 1"	12.5 bar	18,0	20,0	132,0	41
K- 07 30 26 83	G 1"	13.0 bar	18,0	20,0	132,0	41
K- 07 30 26 84	G 1"	14.0 bar	18,0	20,0	132,0	41
K- 07 30 26 85	G 1"	14.5 bar	18,0	20,0	132,0	41
K- 07 30 26 86	G 1"	15.0 bar	18,0	20,0	132,0	41
K- 07 30 26 87	G 1"	15.5 bar	18,0	20,0	132,0	41

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.

Article

Désignation	Filets	Pression de réponse	a (mm)	do (mm)	H (mm)	SW (mm)
K- 07 30 26 88	G 1"	16.0 bar	18,0	20,0	132,0	41
K- 07 30 26 89	G 1"	16.5 bar	18,0	20,0	132,0	41
K- 07 30 26 90	G 1"	17.0 bar	18,0	20,0	132,0	41
K- 07 30 26 91	G 1"	18.0 bar	18,0	20,0	132,0	41
K- 07 30 26 96	G 1"	20.0 bar	18,0	20,0	132,0	41
K- 07 30 26 97	G 1"	25.0 bar	18,0	20,0	132,0	41
K- 07 30 26 98	G 1"	26.0 bar	18,0	20,0	132,0	41
K- 07 30 27 22	G 1 1/4"	0.2 bar	20,0	25,0	152,0	50
K- 07 30 27 23	G 1 1/4"	0.5 bar	20,0	25,0	152,0	50
K- 07 30 27 24	G 1 1/4"	0.6 bar	20,0	25,0	152,0	50
K- 07 30 27 25	G 1 1/4"	0.8 bar	20,0	25,0	152,0	50
K- 07 30 27 26	G 1 1/4"	1.0 bar	20,0	25,0	152,0	50
K- 07 30 27 27	G 1 1/4"	1.1 bar	20,0	25,0	152,0	50
K- 07 30 27 28	G 1 1/4"	1.5 bar	20,0	25,0	152,0	50
K- 07 30 27 39	G 1 1/4"	2.0 bar	20,0	25,0	152,0	50
K- 07 30 27 40	G 1 1/4"	2.3 bar	20,0	25,0	152,0	50
K- 07 30 27 41	G 1 1/4"	2.5 bar	20,0	25,0	152,0	50
K- 07 30 27 43	G 1 1/4"	3.0 bar	20,0	25,0	152,0	50
K- 07 30 27 44	G 1 1/4"	4.0 bar	20,0	25,0	152,0	50
K- 07 30 27 45	G 1 1/4"	4.5 bar	20,0	25,0	152,0	50
K- 07 30 27 46	G 1 1/4"	5.0 bar	20,0	25,0	152,0	50
K- 07 30 27 47	G 1 1/4"	6.0 bar	20,0	25,0	152,0	50
K- 07 30 27 48	G 1 1/4"	6.3 bar	20,0	25,0	152,0	50
K- 07 30 27 49	G 1 1/4"	6.5 bar	20,0	25,0	152,0	50
K- 07 30 27 50	G 1 1/4"	7.0 bar	20,0	25,0	152,0	50
K- 07 30 27 51	G 1 1/4"	7.5 bar	20,0	25,0	152,0	50
K- 07 30 27 52	G 1 1/4"	8.0 bar	20,0	25,0	152,0	50
K- 07 30 27 53	G 1 1/4"	8.5 bar	20,0	25,0	152,0	50
K- 07 30 27 54	G 1 1/4"	8.8 bar	20,0	25,0	152,0	50
K- 07 30 27 55	G 1 1/4"	9.0 bar	20,0	25,0	152,0	50
K- 07 30 27 56	G 1 1/4"	9.5 bar	20,0	25,0	152,0	50
K- 07 30 27 29	G 1 1/4"	10.0 bar	20,0	25,0	152,0	50
K- 07 30 27 30	G 1 1/4"	10.5 bar	20,0	25,0	152,0	50
K- 07 30 27 31	G 1 1/4"	11.0 bar	20,0	25,0	152,0	50
K- 07 30 27 32	G 1 1/4"	12.0 bar	20,0	25,0	152,0	50
K- 07 30 27 33	G 1 1/4"	13.0 bar	20,0	25,0	152,0	50
K- 07 30 27 34	G 1 1/4"	14.0 bar	20,0	25,0	152,0	50
K- 07 30 27 35	G 1 1/4"	15.0 bar	20,0	25,0	152,0	50
K- 07 30 27 36	G 1 1/4"	16.0 bar	20,0	25,0	152,0	50
K- 07 30 27 37	G 1 1/4"	17.0 bar	20,0	25,0	152,0	50
K- 07 30 27 38	G 1 1/4"	18.0 bar	20,0	25,0	152,0	50
K- 07 30 27 42	G 1 1/4"	22.0 bar	20,0	25,0	152,0	50
K- 07 30 27 57	G 1 1/2"	0.2 bar	22,0	32,0	178,0	55
K- 07 30 27 58	G 1 1/2"	0.4 bar	22,0	32,0	178,0	55
K- 07 30 27 59	G 1 1/2"	0.5 bar	22,0	32,0	178,0	55
K- 07 30 27 60	G 1 1/2"	0.6 bar	22,0	32,0	178,0	55
K- 07 30 27 61	G 1 1/2"	0.65 bar	22,0	32,0	178,0	55
K- 07 30 27 62	G 1 1/2"	0.75 bar	22,0	32,0	178,0	55
K- 07 30 27 63	G 1 1/2"	0.8 bar	22,0	32,0	178,0	55
K- 07 30 27 64	G 1 1/2"	0.9 bar	22,0	32,0	178,0	55
K- 07 30 27 65	G 1 1/2"	1.0 bar	22,0	32,0	178,0	55
K- 07 30 27 66	G 1 1/2"	1.5 bar	22,0	32,0	178,0	55
K- 07 30 27 67	G 1 1/2"	1.6 bar	22,0	32,0	178,0	55
K- 07 30 27 77	G 1 1/2"	2.0 bar	22,0	32,0	178,0	55
K- 07 30 27 78	G 1 1/2"	2.1 bar	22,0	32,0	178,0	55
K- 07 30 27 79	G 1 1/2"	2.3 bar	22,0	32,0	178,0	55
K- 07 30 27 80	G 1 1/2"	2.5 bar	22,0	32,0	178,0	55
K- 07 30 27 81	G 1 1/2"	2.6 bar	22,0	32,0	178,0	55
K- 07 30 27 82	G 1 1/2"	3.0 bar	22,0	32,0	178,0	55
K- 07 30 27 83	G 1 1/2"	3.2 bar	22,0	32,0	178,0	55
K- 07 30 27 84	G 1 1/2"	4.0 bar	22,0	32,0	178,0	55
K- 07 30 27 85	G 1 1/2"	4.5 bar	22,0	32,0	178,0	55
K- 07 30 27 86	G 1 1/2"	5.0 bar	22,0	32,0	178,0	55

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.

Article

Désignation	Filets	Pression de réponse	a (mm)	do (mm)	H (mm)	SW (mm)
K- 07 30 27 87	G 1 1/2"	5.8 bar	22,0	32,0	178,0	55
K- 07 30 27 88	G 1 1/2"	6.0 bar	22,0	32,0	178,0	55
K- 07 30 27 89	G 1 1/2"	6.5 bar	22,0	32,0	178,0	55
K- 07 30 27 90	G 1 1/2"	7.0 bar	22,0	32,0	178,0	55
K- 07 30 27 91	G 1 1/2"	7.5 bar	22,0	32,0	178,0	55
K- 07 30 27 92	G 1 1/2"	7.7 bar	22,0	32,0	178,0	55
K- 07 30 27 93	G 1 1/2"	8.0 bar	22,0	32,0	178,0	55
K- 07 30 27 94	G 1 1/2"	8.5 bar	22,0	32,0	178,0	55
K- 07 30 27 95	G 1 1/2"	9.0 bar	22,0	32,0	178,0	55
K- 07 30 27 96	G 1 1/2"	9.5 bar	22,0	32,0	178,0	55
K- 07 30 27 68	G 1 1/2"	10.0 bar	22,0	32,0	178,0	55
K- 07 30 27 69	G 1 1/2"	10.5 bar	22,0	32,0	178,0	55
K- 07 30 27 70	G 1 1/2"	11.0 bar	22,0	32,0	178,0	55
K- 07 30 27 71	G 1 1/2"	12.0 bar	22,0	32,0	178,0	55
K- 07 30 27 72	G 1 1/2"	13.0 bar	22,0	32,0	178,0	55
K- 07 30 27 73	G 1 1/2"	14.0 bar	22,0	32,0	178,0	55
K- 07 30 27 74	G 1 1/2"	14.5 bar	22,0	32,0	178,0	55
K- 07 30 27 75	G 1 1/2"	15.0 bar	22,0	32,0	178,0	55
K- 07 30 27 76	G 1 1/2"	16.0 bar	22,0	32,0	178,0	55
K- 07 30 27 97	G 2"	0.2 bar	25,0	40,0	203,0	70
K- 07 30 27 98	G 2"	0.3 bar	25,0	40,0	203,0	70
K- 07 30 27 99	G 2"	0.4 bar	25,0	40,0	203,0	70
K- 07 30 28 00	G 2"	0.5 bar	25,0	40,0	203,0	70
K- 07 30 28 01	G 2"	0.6 bar	25,0	40,0	203,0	70
K- 07 30 28 02	G 2"	0.7 bar	25,0	40,0	203,0	70
K- 07 30 28 03	G 2"	0.8 bar	25,0	40,0	203,0	70
K- 07 30 28 04	G 2"	1.0 bar	25,0	40,0	203,0	70
K- 07 30 28 05	G 2"	1.2 bar	25,0	40,0	203,0	70
K- 07 30 28 06	G 2"	1.25 bar	25,0	40,0	203,0	70
K- 07 30 28 07	G 2"	1.3 bar	25,0	40,0	203,0	70
K- 07 30 28 08	G 2"	1.4 bar	25,0	40,0	203,0	70
K- 07 30 28 09	G 2"	1.5 bar	25,0	40,0	203,0	70
K- 07 30 28 10	G 2"	1.7 bar	25,0	40,0	203,0	70
K- 07 30 28 11	G 2"	1.8 bar	25,0	40,0	203,0	70
K- 07 30 28 15	G 2"	2.0 bar	25,0	40,0	203,0	70
K- 07 30 28 16	G 2"	2.1 bar	25,0	40,0	203,0	70
K- 07 30 28 17	G 2"	2.2 bar	25,0	40,0	203,0	70
K- 07 30 28 18	G 2"	2.5 bar	25,0	40,0	203,0	70
K- 07 30 28 20	G 2"	3.0 bar	25,0	40,0	203,0	70
K- 07 30 28 21	G 2"	4.0 bar	25,0	40,0	203,0	70
K- 07 30 28 22	G 2"	5.0 bar	25,0	40,0	203,0	70
K- 07 30 28 23	G 2"	6.0 bar	25,0	40,0	203,0	70
K- 07 30 28 24	G 2"	6.5 bar	25,0	40,0	203,0	70
K- 07 30 28 25	G 2"	7.0 bar	25,0	40,0	203,0	70
K- 07 30 28 26	G 2"	7.5 bar	25,0	40,0	203,0	70
K- 07 30 28 27	G 2"	8.0 bar	25,0	40,0	203,0	70
K- 07 30 28 28	G 2"	8.8 bar	25,0	40,0	203,0	70
K- 07 30 28 29	G 2"	9.0 bar	25,0	40,0	203,0	70
K- 07 30 28 30	G 2"	9.3 bar	25,0	40,0	203,0	70
K- 07 30 28 31	G 2"	9.5 bar	25,0	40,0	203,0	70
K- 07 30 28 12	G 2"	10.0 bar	25,0	40,0	203,0	70
K- 07 30 28 13	G 2"	11.0 bar	25,0	40,0	203,0	70
K- 07 30 28 14	G 2"	12.0 bar	25,0	40,0	203,0	70
K- 07 30 28 19	G 2"	25.0 bar	25,0	40,0	203,0	70

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.