

K-SPV DOPPEL

Check valves, double-acting

Caractéristiques

Pression de service	maxi 10 bar
Pression de commande	min. 3.0 bar, max. 8 bar with double-acting actuator; min. 4.2 bar, max. 8 bar for single-drive
Température	-20 °C to +80 °C (NBR); -20 °C to +150 °C (FKM)
Raccord	NAMUR-Interface, direct: 2 x G 1/8
Position de montage	Any
Boîtier, pièces internes	Nickel-plated brass
Ressort	Stainless-steel
Matériau étanche	Perbunan (NBR) or FKM (FPM)



Remarque

Autres informations sur demande.

Description

2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator.
These valves have a full bore.

Article

Désignation	DN	Filets	Matériau étanche	H (mm)	L (mm)
K- 07 30 25 37	10	Rp 3/8	NBR	46,0	98,0
K- 07 30 25 38	15	Rp 1/2	NBR	51,7	112,0
K- 07 30 25 39	20	Rp 3/4	NBR	63,5	135,0
K- 07 30 25 40	25	Rp 1	NBR	69,0	143,0
K- 07 30 25 41	10	Rp 3/8	FKM	46,0	98,0
K- 07 30 25 42	15	Rp 1/2	FKM	51,7	112,0
K- 07 30 25 43	20	Rp 3/4	FKM	63,5	135,0
K- 07 30 25 44	25	Rp 1	FKM	69,0	143,0