


# K-T-TUE

## Tee hose connectors

### Caractéristiques

|                            |   |
|----------------------------|---|
| <b>Pression de service</b> | Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 60 °C) |
| <b>Raccord fileté</b>      | Polyamide (PA)  |
| <b>Anneau de matrice</b>   | Polypropylene (PP)  |
| <b>Écrou</b>               | Polypropylene (PP)  |



### Remarque

Autres informations sur demande.

### Description

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. <br>Not suitable for use with acids.

### Article

| Désignation    | pour tuyau   | L1<br>(mm) | L2<br>(mm) |
|----------------|--------------|------------|------------|
| K- 07 40 32 70 | 4 mm / 6 mm  | 52,0       | 26,0       |
| K- 07 40 32 71 | 6 mm / 8 mm  | 62,0       | 31,0       |
| K- 07 40 32 72 | 8 mm / 10 mm | 72,0       | 36,0       |
| K- 07 40 32 73 | 9 mm / 12 mm | 80,0       | 40,0       |