


# K-VLST 2 X IG MS NI

Extensions, 2 x female thread, parallel - nickel-plated brass

**HANSA FLEX**

## Caractéristiques

|                        |                |
|------------------------|----------------|
| Température de service | Max. 150 °C    |
| Pression               | Max. 60 bar    |
| Matériau               | Laiton nickelé |



## Remarque

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Autres informations sur demande.

## Description

Suitable for air, water, oil, steam, etc.

## Informations supplémentaires

Further types and dimensions on request.

## Article

| Désignation    | Filetage 1 | Filetage 2 | L1<br>(mm) | SW    |
|----------------|------------|------------|------------|-------|
| K- 07 40 39 09 | M 5        | G 1/8      | 13,5       | 14 mm |
| K- 07 40 39 10 | G 1/8      | G 1/4      | 21,5       | 17 mm |
| K- 07 40 39 11 | G 1/8      | G 3/8      | 23,5       | 22 mm |
| K- 07 40 39 12 | G 1/4      | G 3/8      | 25,5       | 22 mm |
| K- 07 40 39 13 | G 1/4      | G 1/2      | 28,5       | 24 mm |
| K- 07 40 39 14 | G 3/8      | G 1/2      | 29,5       | 24 mm |
| K- 07 40 39 15 | G 1/2      | G 3/4      | 30,0       | 32 mm |
| K- 07 40 43 91 | G 1/2      | G 1/8      | 24,0       | 24 mm |
| K- 07 40 43 92 | G 1        | G 3/4      | 25,0       | 38 mm |