K-KONDENSA DRUKODRAIM PLUS

Drain for compressed air condensate

Caractéristiques

Puissance de raccordement filtre	100 m3/min
Puissance de raccordement compresseur	10 m3/min
Puissance de raccordement dessiccateur	20 m3/min



Remarque

Autres informations sur demande.

Description

Compact and exceptionally reliable, level-controlled drain for compressed air condensate. The condensate enters the integrated collecting tank, in which the level is continuously monitored. When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark. Benefits of »drukodrain plus«: No pressure loss, Diaphragm protected by integrated cup filter, Test button for manual outlet, Auto-reset function, Suitable for all condensate types.

Informations relatives à la commande

The following voltages on request: 24 VDC, 24 VAC DC, 24 VAC / 50 Hz, 110 VAC / 50 Hz, 115 V / 50 Hz

Article

Désignation	Pression de service en bar	Tension
K- 07 25 09 24	0.2 - 16 bar	230 VAC / 50 Hz

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.