

K-VT VARIBLOC

Ball valves

HANSA FLEX

Caractéristiques

| | |
|------------------------------|--|
| Départs | 4 (all sealed at delivery) |
| Outlets for G 1/2 and G 3/4 | Top / bottom G 3/8 / G 1/2, Front / back G 1/4 |
| Outlets for G 1/4 and G 3/8 | Top / bottom G 3/8, Front / back G 1/4 |
| Mesure de la valeur du débit | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Remarque

Autres informations sur demande.

Description

For removing unlubricated air when the manifold is flanged on upstream of the oil-mist lubricator. An integrated non-return valve prevents oil inflow from the oil-mist lubricator or the line.

Article

| Désignation | Filets | Débit (L/min) | A (mm) | B |
|----------------|--------|------------------|-----------|---------|
| K- 07 25 11 99 | G 1/4 | 900 | 48,0 | 44,0 mm |
| K- 07 25 12 00 | G 3/8 | 900 | 48,0 | 44,0 mm |
| K- 07 25 12 01 | G 1/2 | 4000 | 70,0 | 56,0 mm |
| K- 07 25 12 02 | G 3/4 | 5000 | 70,0 | 56,0 mm |
| K- 07 25 12 03 | G 1 | 5000 | 124,0 | 56,0 mm |