

# K-VHRO IS OR MS NI

Hexagon socket screw plugs with O-ring

## Caractéristiques

Température de service Max. 80 °C (with O-ring, NBR)

Pression Max. 60 bar

Construction Vis de fermeture à six pans creux

Matériau Laiton nickelé



## Remarque

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Autres informations sur demande.

## Description

Suitable for air, water, oil, steam, etc.

## Informations supplémentaires

Further types and dimensions on request.

## Article

| Désignation    | Filets | six pans creux<br>(mm) | L1<br>(mm) | L2<br>(mm) |
|----------------|--------|------------------------|------------|------------|
| K- 07 40 39 91 | M 5    | 2,5                    | 6,5        | 4,0        |
| K- 07 40 39 92 | G 1/8  | 3,0                    | 9,5        | 7,0        |
| K- 07 40 39 93 | G 1/4  | 6,0                    | 11,0       | 8,0        |
| K- 07 40 39 94 | G 3/8  | 8,0                    | 12,5       | 9,0        |
| K- 07 40 39 95 | G 1/2  | 10,0                   | 14,5       | 11,0       |
| K- 07 40 44 09 | G 3/4  | 17,0                   | 20,0       | 15,5       |
| K- 07 40 44 10 | G 1    | 19,0                   | 21,0       | 16,0       |