

K-VT 2 KUPPL 7,2 STECKNIP MS

Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8

HANSA FLEX

Caractéristiques

Pression de service	0 - 35 bar
Température de fluide	-20 °C to +100 °C
Boîtier	Brass
Fixation et étanchéité	Industrial glue, mid hardened



Remarque

Couplings and distributors are also available separately
Autres informations sur demande.

Description

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Informations supplémentaires

Couplings and distributors are also available separately

Article

Désignation	Raccord	Accouplement	constitué d'une distribution
K- 07 40 40 48	Plugs DN 7.2 to 7.8 / G 3/8	K-07350025	K-07404016
K- 07 40 44 27	Plugs DN 7.2 to 7.8 / G 1/2	K-07350026	K-07404017

accessoire pour les produits suivants

K-VSEH 3-KRAFT	Receptacle combinations »3-Kraft«
K-VSEH AIRKRAFT	Receptacle combinations »airkraft«