# K-EINGANGSPL VENTILINSEL HDM

Input plates for HDM valve terminal

## Caractéristiques

| | |
|---|---|
| **Médiums** | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| **Pression de service** | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| **Pression de commande** | 3 - 7 bar |
| **Plage de température** | -10 °C to +60 °C |
| **Débit** | 200 Nl/min (Ø 4), 500 Nl/min (Ø 6), 800 Nl/min (Ø 8) |
| **Nombre de raccordements** | Max. 16 (e.g. 16 spring return valves) |
| **Commande auxiliaire manuelle** | Latching (bistable), Monostable (non-latching) version also available on request |
| **Consommation de puissance** | 0.6 W per pilot |
| **Indice de protection** | IP 65 |



## Remarque

Autres informations sur demande.

## Description

These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates.Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Informations supplémentaires

Important: The scope of supply does not include a connector. Please order separately.

## Article

| Désignation | Fonction | Raccord |
|---|---|---|
| **K- 07 15 22 49** | Standard, internal pilots | Multi-pole |
| **K- 07 15 22 48** | External pilots, dual supply | Multi-pole |
| **K- 07 15 22 54** | Standard, internal pilots | With integrated Profibus DP |
| **K- 07 15 22 53** | External pilots | With integrated Profibus DP |

*En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.*