

# K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,  
CrNi steel type

**HANSA FLEX**

## Caractéristiques

Type	233.50
Fabrication	Glycerine-filled bourdon-tube pressure gauge, CrNi steel type
Application	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
Classe de qualité	1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)
Température de fluide	max. +100 °C
Température ambiante	-20 °C à +60 °C
Boîtier	CrNi steel
Lumière	Laminated safety glass Ø 63 = Polycarbonate



## Remarque

Autres informations sur demande.

## Description

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measuring points with high dynamic pressure loads and vibrations.

## Article

Désignation	Plage de mesure	Ø (mm)	Raccord
K- 07 20 11 93	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 11 95	-1 / +0.6 bar	63,0	G 1/4"
K- 07 20 11 97	-1 / +1.5 bar	63,0	G 1/4"
K- 07 20 11 99	-1 / +3.0 bar	63,0	G 1/4"
K- 07 20 12 01	-1 / +5.0 bar	63,0	G 1/4"
K- 07 20 12 03	-1 / +9.0 bar	63,0	G 1/4"
K- 07 20 12 05	-1 / +15.0 bar	63,0	G 1/4"
K- 07 20 12 08	0 - 1.0 bar	63,0	G 1/4"
K- 07 20 12 10	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 12 12	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 12 14	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 12 16	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 12 18	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 12 20	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 12 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 12 24	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 12 26	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 12 28	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 12 30	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 12 32	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 12 34	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 12 36	0 - 600.0 bar	63,0	G 1/4"
K- 07 20 11 92	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 11 94	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 11 96	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 98	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 12 00	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 12 02	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 12 04	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 12 06	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 12 07	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 12 09	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 12 11	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 12 13	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 12 15	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 12 17	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 12 19	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 12 21	0 - 25.0 bar	100,0	G 1/2"



En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.

23.07.2024

HANSA-FLEX AG

www.hansa-flex.com

1

# K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,  
CrNi steel type

**HANSA FLEX**

## Article

Désignation	Plage de mesure	Ø (mm)	Raccord
K- 07 20 12 23	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 12 25	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 12 27	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 12 29	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 12 31	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 12 33	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 12 35	0 - 600.0 bar	100,0	G 1/2"
K- 07 20 03 48	0 - 0.6 bar	160,0	G 1/2"
K- 07 20 03 49	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 50	0 - 1.6 bar	160,0	G 1/2"
K- 07 20 03 51	0 - 2.5 bar	160,0	G 1/2"
K- 07 20 03 52	0 - 4.0 bar	160,0	G 1/2"
K- 07 20 03 53	0 - 6.0 bar	160,0	G 1/2"
K- 07 20 03 54	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 55	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 56	0 - 25.0 bar	160,0	G 1/2"
K- 07 20 03 57	0 - 40.0 bar	160,0	G 1/2"
K- 07 20 03 58	0 - 60.0 bar	160,0	G 1/2"
K- 07 20 03 59	0 - 100.0 bar	160,0	G 1/2"
K- 07 20 03 60	0 - 160.0 bar	160,0	G 1/2"
K- 07 20 03 61	0 - 250.0 bar	160,0	G 1/2"
K- 07 20 03 62	0 - 400.0 bar	160,0	G 1/2"
K- 07 20 03 63	0 - 600.0 bar	160,0	G 1/2"