

K-LKM S NW7,4 IG

Safety couplings DN 7.4, female

Caractéristiques

Pression de service	Max. 12 bar, maximum static working pressure (non-pulsating)
Pression de service douilles embrochables et mamelons	0 to 35 bar
Débit d'air	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Température de fluide	-20 °C to +60 °C
Boîtier, corps de vanne	Nickel-plated brass
Vanne	Brass
Manchon de déverrouillage	Plastic
Ressort, circlip, goupilles, sphères	Stainless steel
Matériau étanche	NBR



Remarque

Autres informations sur demande.

Description

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

Article

Désignation	Raccord	Longueur (mm)	SW (mm)
K- 07 35 03 01	G 1/4 female	57,2	22
K- 07 35 03 02	G 3/8 female	60,2	24
K- 07 35 03 03	G 1/2 female	60,2	24

Accessoires

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,