


# K-LKM S NW7,4 SCHL TUE

Safety couplings DN 7.4, with hose stem

**HANSA FLEX**

## Caractéristiques

<b>Pression de service</b>	Max. 12 bar, maximum static working pressure (non-pulsating)
<b>Pression de service douilles embrochables et mamelons</b>	0 to 35 bar
<b>Débit d'air</b>	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Température de fluide</b>	-20 °C to +60 °C
<b>Boîtier, corps de vanne</b>	Nickel-plated brass
<b>Vanne</b>	Brass
<b>Manchon de déverrouillage</b>	Plastic
<b>Ressort, circlip, goupilles, sphères</b>	Stainless steel
<b>Matériau étanche</b>	NBR



## Remarque

Autres informations sur demande.

## Description

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

## Article

Désignation	Raccord	Longueur (mm)	SW (mm)
K- 07 35 03 04	Stem, I.D. 6	71,2	22
K- 07 35 03 05	Stem, I.D. 8	71,2	22
K- 07 35 03 06	Stem, I.D. 9	71,2	22
K- 07 35 03 07	Stem, I.D. 10	71,2	22
K- 07 35 03 08	Stem, I.D. 13	71,2	22

## Accessoires

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,