K-DMUF ALLGEMEIN

Pressure transmitters for universal industrial applications, nonlinearity 0.25%

Caractéristiques

Type	S-20
Tension	DC 8 ... 36 V
Raccord électrique	With right-angle connector acc. to DIN EN 175301-803 A
Indice de protection	IP 65 acc. to EN 60529
Signal de sortie	4 to 20 mA, 2-wire
Non-linéarité	up to 0.25% of span
Température de fluide	-30 °C to +100 °C
Température ambiante	-40 °C to +70 °C
Parties en contact avec le fluide	CrNi steel 1.4571
Boîtier	CrNi steel 1.4571



Description

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development. Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry. Compatible with all internationally established process connections.

Informations supplémentaires

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Article

Désignation	Plage de mesure	Filets
K- 07 20 12 55	-1 / 0.0 bar	G 1/2
K- 07 20 12 56	0 - 0.4 bar	G 1/2
K- 07 20 12 57	0 - 1.0 bar	G 1/2
K- 07 20 12 64	0 - 4.0 bar	G 1/2
K- 07 20 12 67	0 - 6.0 bar	G 1/2
K- 07 20 12 58	0 - 10.0 bar	G 1/2
K- 07 20 12 60	0 - 16.0 bar	G 1/2
K- 07 20 12 62	0 - 25.0 bar	G 1/2
K- 07 20 12 65	0 - 40.0 bar	G 1/2
K- 07 20 12 68	0 - 60.0 bar	G 1/2
K- 07 20 12 59	0 - 100.0 bar	G 1/2
K- 07 20 12 61	0 - 160.0 bar	G 1/2
K- 07 20 12 63	0 - 250.0 bar	G 1/2
K- 07 20 12 66	0 - 400.0 bar	G 1/2
K- 07 20 12 69	0 - 600.0 bar	G 1/2

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.