

K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

HANSA FLEX

Caractéristiques

| | |
|-------------------------------|---|
| Médiums | Air, neutral gases, filtered |
| Pression de service | 0.5 to 10 bar |
| Température de service | -20 °C to +70 °C |
| joint à la livraison | 1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws |
| Boîtier | Aluminium, anodised |
| Matériau | Joint : NBR |
| Matériau étanche | NBR |



Remarque

Autres informations sur demande.

Description

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

Article

| Désignation | Fonction | Actionnement | DN | Débit (L/min) |
|----------------|----------|---------------|----|------------------|
| K- 07 15 22 39 | 3/2-way | Knurled Screw | 5 | 650 |
| K- 07 15 22 40 | 3/2-way | Screwdriver | 5 | 650 |
| K- 07 15 22 41 | 5/2-way | Knurled Screw | 5 | 650 |
| K- 07 15 22 42 | 5/2-way | Screwdriver | 5 | 650 |