K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

Caractéristiques

Médiums	Filtered, unlubricated compressed air
Pression de service	2.5 - 8 bar
Plage de température	-10 °C to +60 °C
Raccord	Push-in fitting for pipe 4 mm
Actionnement	Pneumatic
Débit air 6 bar	85 Nl/min
Décalage maxi signal d'entrée	0,4 s



Remarque

Autres informations sur demande.

Description

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter.Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Article

Désignation	Définition	Raccord
K- 07 15 26 09	Two-hand safety valve without housing	Push-in fitting for 4 mm pipe
K- 07 15 26 10	mounting element	-

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.