

# K-MANO STAND U

Pressure gauges, CrNi steel, standard type, connection radial on bottom

**HANSA FLEX**

## Caractéristiques

|                       |   |
|-----------------------|---|
| Type                  | 131.11  |
| Fabrication           | Bourdon-tube pressure gauge, CrNi steel type  |
| Application           | For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere<br>Clean Dry Air applications, machine and plant construction |
| Classe de qualité     | 2,5   |
| Température de fluide | max. +100 °C  |
| Température ambiante  | -40 °C to +60 °C  |
| Boîtier               | CrNi steel  |
| Lumière               | Polycarbonate   |



## Remarque

Autres informations sur demande.

## Description

Standard model manufactured entirely from CrNi steel, economical and reliable.

## Article

| Désignation    | Plage de mesure | Ø (mm) | Raccord |
|----------------|-----------------|--------|---------|
| K- 07 20 03 82 | 0 - 1.0 bar     | 40,0   | G 1/4   |
| K- 07 20 03 83 | 0 - 1.6 bar     | 40,0   | G 1/4   |
| K- 07 20 03 84 | 0 - 2.5 bar     | 40,0   | G 1/4   |
| K- 07 20 03 85 | 0 - 4.0 bar     | 40,0   | G 1/4   |
| K- 07 20 03 86 | 0 - 6.0 bar     | 40,0   | G 1/4   |
| K- 07 20 03 87 | 0 - 10.0 bar    | 40,0   | G 1/4   |
| K- 07 20 03 88 | 0 - 16.0 bar    | 40,0   | G 1/4   |
| K- 07 20 03 89 | 0 - 25.0 bar    | 40,0   | G 1/4   |
| K- 07 20 03 90 | 0 - 40.0 bar    | 40,0   | G 1/4   |
| K- 07 20 03 91 | 0 - 60.0 bar    | 40,0   | G 1/4   |
| K- 07 20 03 92 | 0 - 100.0 bar   | 40,0   | G 1/4   |
| K- 07 20 04 83 | 0 - 1.0 bar     | 50,0   | G 1/4   |
| K- 07 20 04 84 | 0 - 1.6 bar     | 50,0   | G 1/4   |
| K- 07 20 04 85 | 0 - 2.5 bar     | 50,0   | G 1/4   |
| K- 07 20 04 86 | 0 - 4.0 bar     | 50,0   | G 1/4   |
| K- 07 20 04 87 | 0 - 6.0 bar     | 50,0   | G 1/4   |
| K- 07 20 04 88 | 0 - 10.0 bar    | 50,0   | G 1/4   |
| K- 07 20 04 89 | 0 - 16.0 bar    | 50,0   | G 1/4   |
| K- 07 20 04 90 | 0 - 25.0 bar    | 50,0   | G 1/4   |
| K- 07 20 04 91 | 0 - 40.0 bar    | 50,0   | G 1/4   |
| K- 07 20 04 92 | 0 - 60.0 bar    | 50,0   | G 1/4   |
| K- 07 20 04 93 | 0 - 100.0 bar   | 50,0   | G 1/4   |