

# K-MANO STAND U

Pressure gauges, CrNi steel, standard type, connection radial on bottom

**HANSA FLEX**

## Caractéristiques

Type	131.11
Fabrication	Bourdon-tube pressure gauge, CrNi steel type
Application	For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere Clean Dry Air applications, machine and plant construction
Classe de qualité	2,5
Température de fluide	max. +100 °C
Température ambiante	-40 °C to +60 °C
Boîtier	CrNi steel
Lumière	Polycarbonate



## Remarque

Autres informations sur demande.

## Description

Standard model manufactured entirely from CrNi steel, economical and reliable.

## Article

Désignation	Plage de mesure	Ø (mm)	Raccord
K- 07 20 03 82	0 - 1.0 bar	40,0	G 1/4
K- 07 20 03 83	0 - 1.6 bar	40,0	G 1/4
K- 07 20 03 84	0 - 2.5 bar	40,0	G 1/4
K- 07 20 03 85	0 - 4.0 bar	40,0	G 1/4
K- 07 20 03 86	0 - 6.0 bar	40,0	G 1/4
K- 07 20 03 87	0 - 10.0 bar	40,0	G 1/4
K- 07 20 03 88	0 - 16.0 bar	40,0	G 1/4
K- 07 20 03 89	0 - 25.0 bar	40,0	G 1/4
K- 07 20 03 90	0 - 40.0 bar	40,0	G 1/4
K- 07 20 03 91	0 - 60.0 bar	40,0	G 1/4
K- 07 20 03 92	0 - 100.0 bar	40,0	G 1/4
K- 07 20 04 83	0 - 1.0 bar	50,0	G 1/4
K- 07 20 04 84	0 - 1.6 bar	50,0	G 1/4
K- 07 20 04 85	0 - 2.5 bar	50,0	G 1/4
K- 07 20 04 86	0 - 4.0 bar	50,0	G 1/4
K- 07 20 04 87	0 - 6.0 bar	50,0	G 1/4
K- 07 20 04 88	0 - 10.0 bar	50,0	G 1/4
K- 07 20 04 89	0 - 16.0 bar	50,0	G 1/4
K- 07 20 04 90	0 - 25.0 bar	50,0	G 1/4
K- 07 20 04 91	0 - 40.0 bar	50,0	G 1/4
K- 07 20 04 92	0 - 60.0 bar	50,0	G 1/4
K- 07 20 04 93	0 - 100.0 bar	50,0	G 1/4