

K-SVKM NW 7,8 SCHL TUE H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem

HANSA FLEX

Caractéristiques

Pression de service	0 - 35 bar
Débit d'air	2.100 l/min (at $\Delta p = 0.5$ bar)
Température de fluide	-20 °C to +40 °C
Pièce filetée	Nickel-plated brass
Corps de vanne	Steel, QPQ treated
Manchon de déverrouillage	Extremely robust, ergonomic plastic
Vanne, siège	Brass
Médiums	Only for clean compressed air
Joints	NBR
Ressort, circlip, sphères	stain less steel



Remarque

Autres informations sur demande.

Description

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Article

Désignation	Raccord	Longueur (mm)	SW (mm)
K- 07 35 08 53	Stem, I.D. 6	80,0	19
K- 07 35 12 41	Stem, I.D. 8	80,0	19
K- 07 35 08 54	Stem, I.D. 9	80,0	19
K- 07 35 12 42	Stem, I.D. 10	80,0	19
K- 07 35 08 55	Stem, I.D. 13	80,0	19

Accessoires

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass