


# K-SVKM NW 7,2 SCHL-ANSCHL MS

Quick disconnect couplings DN 7.2, nickel-plated brass, with hose connector, with swivel nut

**HANSA FLEX**

## Caractéristiques

<b>Pression de service</b>	0 - 35 bar, maximum static working pressure (non-pulsating)
<b>Débit d'air</b>	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Température de fluide</b>	-20 °C to +100 °C
<b>Boîtier, douille</b>	Nickel-plated brass
<b>Vanne</b>	Brass with a bare metal surface
<b>Ressort, circlip</b>	Stainless steel 1.4310
<b>Tiges de verrouillage</b>	Stainless steel 1.4034
<b>Matériau étanche</b>	NBR



## Remarque

Autres informations sur demande.

## Description

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

## Article

Désignation	Raccord	Longueur (mm)	SW (mm)
K- 07 35 12 67	Hose connection 6 x 4	58,0	21
K- 07 35 07 24	Hose connection 8 x 6	45,0	21
K- 07 35 07 25	Hose connection 10 x 8	49,0	21
K- 07 35 07 26	Hose connection 12 x 9	49,0	21

## Accessoires

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass