

# K-RD STUECKE POM

Reducers

**HANSA FLEX**

## Caractéristiques

|                        |   |
|------------------------|---|
| Pression de service    | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)    |
| Température de service | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| Matériau               | Acetalpolymerisat (POM)                           |
| Matériau étanche       | NBR   |



## Remarque

Autres informations sur demande.

## Description

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

## Article

| Désignation    | pour Ø ext. du tuyau | L1<br>(mm) | Manchons<br>(mm) |
|----------------|----------------------|------------|------------------|
| K- 07 40 28 91 | 8 mm                 | 46,7       | 12               |
| K- 07 40 28 92 | 10 mm                | 50,9       | 12               |
| K- 07 40 28 93 | 10 mm                | 61,2       | 15               |
| K- 07 40 28 94 | 12 mm                | 61,2       | 15               |
| K- 07 40 28 95 | 15 mm                | 71,7       | 18               |
| K- 07 40 28 96 | 15 mm                | 72,7       | 22               |
| K- 07 40 28 97 | 18 mm                | 71,8       | 22               |
| K- 07 40 28 98 | 15 mm                | 81,4       | 28               |
| K- 07 40 28 99 | 22 mm                | 82,6       | 28               |