


# K-STECKNIPPEL RED

push-in plugs, unequal

**HANSA FLEX**

## Caractéristiques

<b>Pression de service</b>	Max. 15 bar, coarse vacuum
<b>Domaine d'utilisation</b>	Air, vacuum
<b>Tuyaux recommandés</b>	PU or PA (nylon)
<b>Médiums</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Plage de température</b>	-20 °C to +80 °C
<b>Surface d'étanchéité</b>	Parallel version: O-ring in housing, Conical version: thread coating
<b>Matériau</b>	Plastic, Nickel plated brass
<b>Bague de pression</b>	Plastic



## Remarque

Autres informations sur demande.

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Article

Désignation	pour Ø ext. du tuyau	L1 (mm)
K- 07 40 42 83	6 mm / 4 mm	37,5
K- 07 40 42 84	8 mm / 4 mm	40,5
K- 07 40 42 85	8 mm / 6 mm	42,5
K- 07 40 42 86	10 mm / 6 mm	44,5
K- 07 40 42 87	10 mm / 8 mm	47,0
K- 07 40 42 88	12 mm / 8 mm	49,5
K- 07 40 42 89	12 mm / 10 mm	51,0