

# K-STECKNIPPEL RED

push-in plugs, unequal

**HANSA FLEX**

## Caractéristiques

|                              |  |
|------------------------------|--|
| <b>Pression de service</b>   | Max. 15 bar, coarse vacuum   |
| <b>Domaine d'utilisation</b> | Air, vacuum  |
| <b>Tuyaux recommandés</b>    | PU or PA (nylon)   |
| <b>Médiums</b>               | Compressed air and all gases or liquids that are compatible with the materials |
| <b>Plage de température</b>  | -20 °C to +80 °C   |
| <b>Surface d'étanchéité</b>  | Parallel version: O-ring in housing, Conical version: thread coating           |
| <b>Matériau</b>              | Plastic, Nickel plated brass   |
| <b>Bague de pression</b>     | Plastic  |



## Remarque

Autres informations sur demande.

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Article

| Désignation    | pour Ø ext. du tuyau | L1<br>(mm) |
|----------------|----------------------|------------|
| K- 07 40 42 83 | 6 mm / 4 mm          | 37,5       |
| K- 07 40 42 84 | 8 mm / 4 mm          | 40,5       |
| K- 07 40 42 85 | 8 mm / 6 mm          | 42,5       |
| K- 07 40 42 86 | 10 mm / 6 mm         | 44,5       |
| K- 07 40 42 87 | 10 mm / 8 mm         | 47,0       |
| K- 07 40 42 88 | 12 mm / 8 mm         | 49,5       |
| K- 07 40 42 89 | 12 mm / 10 mm        | 51,0       |