

# K-SVKM NW 2,7 SCHL VA

Quick disconnect couplings DN 2.7, stainless steel 1.4404, with hose connector

**HANSA FLEX**

## Caractéristiques

|                                  |                                                             |
|----------------------------------|-------------------------------------------------------------|
| Pression de service              | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Débit d'air                      | 165 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| Température de fluide            | -15 °C to +200 °C                                           |
| Boîtier, douille, corps de vanne | Stainless steel 1.4404                                      |
| Ressort, circlip, sphères        | Stainless steel 1.4404                                      |
| Matériau étanche                 | FKM                                                         |



## Remarque

Autres informations sur demande.

## Description

One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. Ideal for: Medical equipment, chemical and pharmaceutical industry, laboratories, plant construction and butchers.

## Article

| Désignation    | Raccord               | Longueur<br>(mm) | SW<br>(mm) |
|----------------|-----------------------|------------------|------------|
| K- 07 35 12 51 | Hose connection 4 x 3 | 34,0             | 9          |
| K- 07 35 12 52 | Hose connection 5 x 3 | 34,0             | 9          |
| K- 07 35 12 53 | Hose connection 6 x 4 | 34,0             | 9          |