

# K-L-MEHRFACHVERT 4 DR AGR-K

Multiple union elbows with outer hex, 4 outlets, swivel type, conical male thread, coated

**HANSA FLEX**

## Caractéristiques

|                       |  |
|-----------------------|--|
| Pression de service   | Max. 15 bar, coarse vacuum   |
| Domaine d'utilisation | Air, vacuum  |
| Tuyaux recommandés    | PU or PA (nylon)   |
| Médiums               | Compressed air and all gases or liquids that are compatible with the materials |
| Plage de température  | -20 °C to +80 °C   |
| Surface d'étanchéité  | Conical version: thread coating  |
| Matériau              | Plastic, Nickel plated brass   |
| Bague de pression     | Plastic  |



## Remarque

Autres informations sur demande.

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Article

| Désignation    | Filets | pour Ø ext. du tuyau | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|--------|----------------------|------------|------------|-------|
| K- 07 40 43 37 | R 1/8  | 6 mm                 | 38,5       | 24,0       | 12 mm |
| K- 07 40 43 38 | R 1/8  | 8 mm                 | 41,6       | 28,5       | 14 mm |
| K- 07 40 43 35 | R 1/4  | 6 mm                 | 40,5       | 24,0       | 14 mm |
| K- 07 40 43 36 | R 1/4  | 8 mm                 | 43,6       | 28,5       | 14 mm |
| K- 07 40 43 34 | R 1/4  | 10 mm                | 52,8       | 33,7       | 19 mm |
| K- 07 40 43 39 | R 3/8  | 10 mm                | 53,8       | 33,7       | 19 mm |
| K- 07 40 43 40 | R 3/8  | 12 mm                | 61,0       | 37,5       | 24 mm |
| K- 07 40 43 33 | R 1/2  | 12 mm                | 64,0       | 37,5       | 24 mm |