

K-LKM S NW7,4 DREH SCHL TUE VA

Safety couplings DN 7.4, stainless steel 1.4404, with hose stem, swivel type

HANSA FLEX

Caractéristiques

Pression de service	maxi 10 bar
Débit d'air	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Température de fluide	-20 °C to +150 °C
Boîtier	Stainless steel 1.4404
Filets	Stainless steel 1.4404
Pièces internes	Stainless steel 1.4404
Bouton, vanne	Stainless steel 1.4404
Matériau étanche	FKM



Remarque

Not suitable for hitting / pulsating tools.
Autres informations sur demande.

Description

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Informations supplémentaires

Not suitable for hitting / pulsating tools.

Article

Désignation	Raccord	Longueur (mm)	SW (mm)
K- 07 35 12 83	Stem, I.D. 6	88,5	21
K- 07 35 12 85	Stem, I.D. 9	88,5	21
K- 07 35 12 86	Stem, I.D. 13	88,5	21