


# K-STECKVERSCHR IG SK

Male connectors, parallel female thread with outer hex

**HANSA FLEX**

## Caractéristiques

|                        |                  |
|------------------------|------------------|
| Pression de service    | Max. 16 bar      |
| Température de service | -20 °C to +80 °C |
| Matériau               | Laiton nickelé   |
| Bague de pression      | Hostaform        |
| Circlip                | Stainless steel  |



## Remarque

Autres informations sur demande.

## Description

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Article

| Désignation    | Filets | pour Ø ext. du tuyau | L1<br>(mm) | SW    |
|----------------|--------|----------------------|------------|-------|
| K- 07 40 25 06 | M 5    | 3 mm                 | 15,7       | 7 mm  |
| K- 07 40 25 12 | G 1/8  | 4 mm                 | 26,2       | 10 mm |
| K- 07 40 25 13 | G 1/8  | 5 mm                 | 27,5       | 12 mm |
| K- 07 40 25 14 | G 1/8  | 6 mm                 | 27,1       | 12 mm |
| K- 07 40 25 15 | G 1/8  | 8 mm                 | 28,1       | 13 mm |
| K- 07 40 25 09 | G 1/4  | 4 mm                 | 28,6       | 10 mm |
| K- 07 40 47 15 | G 1/4  | 5 mm                 | 29,5       | 12 mm |
| K- 07 40 25 10 | G 1/4  | 6 mm                 | 29,3       | 12 mm |
| K- 07 40 25 11 | G 1/4  | 8 mm                 | 30,0       | 14 mm |
| K- 07 40 25 08 | G 1/4  | 10 mm                | 31,8       | 16 mm |
| K- 07 40 25 16 | G 3/8  | 10 mm                | 36,8       | 16 mm |
| K- 07 40 25 17 | G 3/8  | 12 mm                | 37,0       | 19 mm |
| K- 07 40 25 07 | G 1/2  | 12 mm                | 40,5       | 19 mm |