


# K-SCHOTT-STECKVERB 3

Female bulkhead connectors

**HANSA FLEX**

## Caractéristiques

|                       |  |
|-----------------------|--|
| Pression de service   | Max. 15 bar, coarse vacuum   |
| Domaine d'utilisation | Air, vacuum  |
| Tuyaux recommandés    | PU or PA (nylon)   |
| Médiums               | Compressed air and all gases or liquids that are compatible with the materials |
| Plage de température  | -20 °C to +80 °C   |
| Matériau              | Plastic, Nickel plated brass   |
| Bague de pression     | Plastic  |



## Remarque

Autres informations sur demande.

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Article

| Désignation    | pour Ø ext. du tuyau | Filetage tableau de commande | L1<br>(mm) | SW    |
|----------------|----------------------|------------------------------|------------|-------|
| K- 07 40 04 31 | 4 mm                 | M 12 x 1                     | 31,1       | 14 mm |
| K- 07 40 04 32 | 6 mm                 | M 14 x 1                     | 33,4       | 17 mm |
| K- 07 40 04 33 | 8 mm                 | M 16 x 1                     | 37,7       | 19 mm |
| K- 07 40 04 34 | 10 mm                | M 20 x 1                     | 41,8       | 24 mm |
| K- 07 40 04 35 | 12 mm                | M 22 x 1                     | 46,7       | 27 mm |
| K- 07 40 04 36 | 16 mm                | M 27 x 1                     | 51,2       | 32 mm |