

# K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick disconnect couplings and stems DN 7.2

**HANSA FLEX**

## Caractéristiques

Couche intérieure	Soft-PVC, black
Revêtement	Tresse polyester
Couche extérieure	Soft-PVC, blue
Température de service	-20 °C to +60 °C



## Remarque

Autres informations sur demande.

## Description

Highly flexible hose for compressed air applications in workshop areas. Assembled with brass stem and brass quick disconnect coupling DN 7.2

## Article

Désignation	Ø tuyau intérieur (mm)	Ø tuyau extérieur (mm)	Pression de service maxi à 20 °C (bar)	Longueur de tuyau (m)
K- 07 10 11 91	6,3	11,0	15	5
K- 07 10 11 85	6,3	11,0	15	10
K- 07 10 11 87	6,3	11,0	15	15
K- 07 10 11 88	6,3	11,0	15	20
K- 07 10 11 90	6,3	11,0	15	25
K- 07 10 11 99	9,0	14,5	15	5
K- 07 10 11 93	9,0	14,5	15	10
K- 07 10 11 95	9,0	14,5	15	15
K- 07 10 11 96	9,0	14,5	15	20
K- 07 10 11 98	9,0	14,5	15	25