

K-T-STECK VB

Union tees

HANSA FLEX

Caractéristiques

| | |
|-----------------------|--|
| Pression de service | Max. 15 bar, coarse vacuum |
| Domaine d'utilisation | Air, vacuum |
| Tuyaux recommandés | PU or PA (nylon) |
| Médiums | Compressed air and all gases or liquids that are compatible with the materials |
| Plage de température | -20 °C to +80 °C |
| Matériau | Plastic, Nickel plated brass |
| Bague de pression | Plastic |



Remarque

Autres informations sur demande.

Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Article

| Désignation | pour Ø ext. du tuyau | L1 (mm) |
|----------------|----------------------|------------|
| K- 07 40 03 56 | 4 mm | 18,5 |
| K- 07 40 03 57 | 6 mm | 19,0 |
| K- 07 40 03 58 | 8 mm | 22,5 |
| K- 07 40 03 59 | 10 mm | 27,9 |
| K- 07 40 03 60 | 12 mm | 29,3 |
| K- 07 40 41 40 | 14 mm | 31,0 |
| K- 07 40 03 61 | 16 mm | 32,5 |