

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Caractéristiques

Couche intérieure	Soft-PVC, black
Revêtement	Tresse polyester
Couche extérieure	Soft-PVC, blue
Température	-20 °C to +60 °C
Longueur des rouleaux	50 m



Remarque

Autres informations sur demande.

Description

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Article

Désignation	Ø tuyau intérieur (mm)	Ø tuyau extérieur (mm)	Max. working pressure resistance at 23°C (bar)	Rayon de courbure min. (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88