


# K-STECKVERBINDU RED 1

Reducers

**HANSA FLEX**

## Caractéristiques

|                        |                  |
|------------------------|------------------|
| Pression de service    | Max. 16 bar      |
| Température de service | -20 °C to +80 °C |
| Matériau               | Laiton nickelé   |
| Bague de pression      | Hostaform        |
| Circlip                | Stainless steel  |



## Remarque

Autres informations sur demande.

## Description

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Article

| Désignation    | Filets   | pour Ø ext. du tuyau | L1<br>(mm) |
|----------------|----------|----------------------|------------|
| K- 07 40 25 26 | M 13 x 1 | 4 mm / 6 mm          | 32,7       |
| K- 07 40 25 27 | M 15 x 1 | 4 mm / 8 mm          | 34,4       |
| K- 07 40 25 28 | M 15 x 1 | 6 mm / 8 mm          | 35,0       |
| K- 07 40 25 29 | M 17 x 1 | 6 mm / 10 mm         | 37,5       |
| K- 07 40 25 30 | M 20 x 1 | 6 mm / 12 mm         | 39,0       |
| K- 07 40 25 31 | M 17 x 1 | 8 mm / 10 mm         | 37,8       |
| K- 07 40 25 32 | M 20 x 1 | 8 mm / 12 mm         | 40,1       |
| K- 07 40 25 33 | M 20 x 1 | 10 mm / 12 mm        | 40,8       |