

K-DLV MULTI-LINK OHNE KUPPLU

Compressed air distributor, type »Multi-Link« without couplings, female thread

HANSA FLEX

Caractéristiques

| | |
|----------------------|--|
| Pression de service | Max. 16 bar |
| Plage de température | -20 °C à +100 °C (-20 °C to +80 °C quickconnect-safety couplings) |
| Matériau | Galvanised steel / brass |
| Raccord | G 1/2 female |
| Médiums | Compressed air, non-corrosive gases |
| Matériau étanche | NBR |



Remarque

Autres informations sur demande.

Description

Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 1 to 5 bleed units, optionally with:

- G 1/2 female threaded connection for individually adaption output segments,
- DN 7.6 standard quick disconnect couplings,
- DN 7.6 quick disconnectsafety couplings.

Article

| Désignation | Raccord | Unités de prélèvement |
|----------------|--------------|-----------------------|
| K- 07 35 13 68 | G 1/2 female | 1 |
| K- 07 35 13 71 | G 1/2 female | 2 |
| K- 07 35 13 74 | G 1/2 female | 3 |
| K- 07 35 13 77 | G 1/2 female | 4 |
| K- 07 35 13 80 | G 1/2 female | 5 |