K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

Caractéristiques

Application	Air, gases, oils, greases, fuels, organic and inorganic substances
Température de service	-40 °C to +100 °C
Type de raccordement	connection nipples and coupling NW 7,2



Remarque

Autres informations sur demande.

Description

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Article

Désignation	Ø tuyau intérieur (mm)	Ø tuyau extérieur (mm)	Ø spirale extérieure (mm)	Spires	Max. working pressure resistance at 23° C (bar)	Longueur de travail maxi (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Accessoires

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.