

# K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass

**HANSA FLEX**

## Caractéristiques

Type de raccordement connection nipples and coupling NW 7,2

Température de service -40 °C to +74 °C



## Remarque

Autres informations sur demande.

## Description

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Article

Désignation	Ø tuyau intérieur (mm)	Ø tuyau extérieur (mm)	Ø spire extérieure (mm)	Max. working pressure resistance at 23°C (bar)	Longueur de travail maxi (m)
K- 07 10 12 72	5,0	8,0	40	10	3,0
K- 07 10 12 74	5,0	8,0	40	10	6,0
K- 07 10 12 76	5,0	8,0	40	10	7,5
K- 07 10 12 81	6,3	9,5	60	10	3,0
K- 07 10 12 83	6,3	9,5	60	10	6,0
K- 07 10 12 85	6,3	9,5	60	10	7,5
K- 07 10 12 79	6,3	9,5	60	10	10,0
K- 07 10 12 90	8,0	12,0	80	9	3,0
K- 07 10 12 92	8,0	12,0	80	9	6,0
K- 07 10 12 94	8,0	12,0	80	9	7,5
K- 07 10 12 88	8,0	12,0	80	9	10,0

## Accessoires

K-DREHBARE VERSCHRAUBUNG Swivel adapters