K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

HANSA FLEX

Caractéristiques

Couche intérieure	Soft-PVC, red, oil resistant
Revêtement	Tresse polyester
Couche extérieure	Soft-PVC, black, oil resistant
Température	-20 °C to +60 °C
Longueur des rouleaux	50 m



Remarque

Autres informations sur demande.

Description

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

Article

Désignation	Ø tuyau intérieur (mm)	Ø tuyau extérieur (mm)	Max. working pressure resistance at 23°C (bar)	Rayon de courbure min. (mm)
K- 07 10 10 41	6,3	11,0	16	18
K- 07 10 10 42	8,0	13,0	16	25
K- 07 10 10 43	9,0	14,5	16	25
K- 07 10 10 44	10,0	15,5	16	35
K- 07 10 10 45	12,7	19,0	16	50
K- 07 10 10 46	16,0	23,0	16	70
K- 07 10 10 47	19,0	26,5	16	70
K- 07 10 10 48	25,0	33,5	16	120

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.