

# K-FI HANSA PRO

Compressed air filter, with manual/semi-automatic condensate drain,  
HANSA PRO

**HANSA FLEX**

## Caractéristiques

|                            |  |
|----------------------------|--|
| Température de fluide      | -10 °C to +50 °C                             |
| Température ambiante       | -10 °C to +50 °C                             |
| Médiums                    | Air comprimé                                 |
| Construction               | Centrifugal filter                           |
| Mode de fixation           | Line mounting, mounting kit or wall mounting |
| Position de montage        | Vertical, drain down                         |
| Finesse du filtre          | 5,00 µm                                      |
| Quantité de condensat maxi | 49 cc  |
| Débit nominal G 1/2        | 3.500 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| Débit nominal G 3/8        | 3.500 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| Pe maxi                    | 16 bar                                       |
| Élément de filtre          | Cellpor                                      |
| Boîtier                    | PA66   |



## Article

| Désignation    | Raccord | Réservoir                          | Gabarit | Évacuation du condensat |
|----------------|---------|------------------------------------|---------|-------------------------|
| K- 07 25 21 20 | G 3/8 i | polycarbonate with protective cage | 2       | manual / semi-automatic |
| K- 07 25 21 21 | G 1/2 i | polycarbonate with protective cage | 2       | manual / semi-automatic |
| K- 07 25 21 22 | G 3/8 i | zinc with visual display           | 2       | manual / semi-automatic |
| K- 07 25 21 23 | G 1/2 i | zinc with visual display           | 2       | manual / semi-automatic |