

K-VERTEILER 4-FACH HANSA PRO

Distributor 4-fold, HANSA PRO

HANSA FLEX

Caractéristiques

| | |
|-------------------------------|--|
| Température de fluide | -10 °C to +50 °C |
| Température ambiante | -10 °C to +50 °C |
| Médiums | Air comprimé |
| Mode de fixation | Line mounting, mounting kit or wall mounting |
| Position de montage | Any |
| Débit nominal G 1/2 | 11.000 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Débit nominal G 3/8 | 7.250 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Débit nominal arrière (P - E) | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Débit nominal haut (P - D) | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Débit nominal bas (P - B) | 5.500 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Débit nominal avant (P - C) | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar) |
| PE maxi 11 | 16 bar |
| Boîtier | PA66 |



Article

| Désignation | Raccord P + A | Raccord B | Raccord C | Raccord D | Raccord E | Gabarit |
|----------------|---------------|-----------|-----------|-----------|-----------|---------|
| K- 07 25 22 46 | G 3/8 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 2 |
| K- 07 25 22 47 | G 1/2 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 2 |