

# K-GAM IG VALUE LINE

Female connectors, female thread

**HANSA FLEX**

## Caractéristiques

Pression de service	Max. 16 bar (at +20 °C)
Température de service	-20 °C to +70 °C
Matériau	Laiton nickelé
Bague de pression	Hostaform (black nickel-plated for Ø 10, 12)
Joint torique	NBR, siliconefree
Pince de serrage	Stainless steel AISI 316



## Remarque

Autres informations sur demande.

## Description

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Article

Désignation	Filets	pour Ø ext. du tuyau	L1 (mm)	SW
K- 07 40 29 39	G 1/8	4 mm	26,5	9 mm
K- 07 40 29 38	G 1/4	8 mm	32,0	13 mm
K- 07 40 29 36	G 1/4	10 mm	32,0	16 mm
K- 07 40 29 40	G 1/8	6 mm	27,0	11 mm
K- 07 40 29 41	G 1/8	8 mm	28,0	13 mm
K- 07 40 29 37	G 1/4	6 mm	31,0	11 mm