

No. 1907/2006 (REACH)
Printed 11.12.2015

revision 01.12.2015 (GB) Version 8.2

RIEGLER Rust remover and contact spray / 400 ml

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product RIEGLER Rust remover and contact spray / 400 ml

Code-Nr. 3170/400 / ID-Nr. 114571

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

**Technical Aerosols** 

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor RIEGLER & Co. KG

Schützenstr. 27, D-72574 Bad Urach

Phone: +49 (0) 7125/9497-0, Fax: +49 (0) 7125/9497-97

E-Mail : zedok@riegler.de
Internet : www.riegler.de

Advice Abteilung eDocumentation

Phone : +49 (0) 7125/9497-0 Fax : +49 (0) 7125/9497-97 E-mail (competent person):

zedok@riegler.de

1.4. Emergency telephone number

Emergency advice Giftnotrufzentrale Bonn

Phone : +49(0)228-19 240

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Aerosol 1 H222, H229 Aquatic Chronic 3 H412

**Hazard Statements** 

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.H412 Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02

#### Signal word

Danger

# **Hazard Statements**

H222 Extremely flammable aerosol.



No. 1907/2006 (REACH) Printed 11.12.2015

revision 01.12.2015 (GB) Version 8.2

RIEGLER Rust remover and contact spray / 400 ml

H229	Pressurised container: May burst if heated.
H412	Harmful to aquatic life with long lasting effects.

#### **Precautionary Statements**

P102 Keep out of reach of children.	
·	
P210 Keep away from heat, hot surfaces, sparks, open flames and other igniti P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment.	ion sources. No smoking.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physic	
P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/12 P501 Dispose of contents/container to hazardous or special waste collection p	

### Hazardous ingredients for labeling

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Naphtha (petroleum), hydrotreated heavy

#### 2.3. Other hazards

Product has an anesthetic effect.

### Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

# Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

not applicable

# 3.2. Mixtures

#### Description

Mixture of active ingredients with propellant

# **Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
95-38-5	202-414-9	2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	0,3 - 0,99	Skin Corr. 1B, H314 / Acute Tox. 4, H302 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
74-98-6	200-827-9	propane	10 - 24,99	Flam. Gas 1, H220 / Press. Gas
64742-65-0	265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic	50 - 74,99	Asp. Tox. 1, H304
64742-48-9	265-150-3	Naphtha (petroleum), hydrotreated heavy	10 - 19,99	Asp. Tox. 1, H304
110-25-8	203-749-3	(Z)-N-methyl-N-(1-oxo-9-octadecenyl) glycine	0,3 - 0,99	Eye Dam. 1, H318 / Aquatic Acute 1, H400 / Acute Tox. 4, H332 / Skin Irrit. 2, H315
REACH				
CAS No	Name			REACH registration number
64742-65-0	Distillates (pe	etroleum), solvent-dewaxed heavy paraffinic		01-2119471299-27
64742-48-9	Naphtha (pet	roleum), hydrotreated heavy		01-2119463258-33



No. 1907/2006 (REACH)
Printed 11.12.2015

revision 01.12.2015 (GB) Version 8.2

RIEGLER Rust remover and contact spray / 400 ml

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

### In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

# Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

water mist

#### Unsuitable extinguishing media

Full water jet

# 5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

#### 5.3. Advice for firefighters

# Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

# **Additional information**

Cool endangered containers with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

# For non-emergency personnel

Ensure adequate ventilation.

Keep people away and stay on the upwind side.

Use personal protective clothing.



No. 1907/2006 (REACH)
Printed 11.12.2015

revision 01.12.2015 (GB) Version 8.2

# RIEGLER Rust remover and contact spray / 400 ml

#### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

#### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

#### **Additional Information**

Sort out leaky cans and dispose according to regulations.

#### 6.4. Reference to other sections

Safe handling: see section 7
Disposal: see section 13

Personal protection equipment: see section 8

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

#### Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

#### Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Avoid effect of heat.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

#### Further information on storage conditions

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

#### 7.3. Specific end use(s)

No information available.



No. 1907/2006 (REACH) Printed 11.12.2015

revision 01.12.2015 (GB) Version 8.2

RIEGLER Rust remover and contact spray / 400 ml

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Additional advice**

The statutory local and national regulations have to be observed.

#### 8.2. Exposure controls

#### Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

#### Eye protection

tightly fitting goggles

#### Other protection measures

protective clothing

#### Appropriate engineering controls

Sufficient ventilation and exhaustion.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Appearance Colour Odour aerosol colourless Characteristic

# Odour threshold not determined

#### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not determined				
Ignition temperature	236 °C				
Self ignition temperature					no



No. 1907/2006 (REACH) Printed 11.12.2015

revision 01.12.2015 (GB) Version 8.2

# RIEGLER Rust remover and contact spray / 400 ml

	Value	Temperature	at	Method	Remark
Lower explosion limit	0,7 Vol-%				
Upper explosion limit	10,9 Vol-%				
Vapour pressure	8300 hPa	20 °C			
Relative density	0,803 g/cm3	20 °C			
Vapour density	not determined				
Solubility in water					No or low immiscibility
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	25,2 %				
Solids content	0,3 %				
Ovidising properties					

### **Oxidising properties**

No information available.

# **Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

# 9.2. Other information

No information available.

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

No information available.

# 10.3. Possibility of hazardous reactions

No information available.

### 10.4. Conditions to avoid

Keep away from heat.

Formation of inflammable vapour-air mixtures.

### 10.5. Incompatible materials

No information available.

# 10.6. Hazardous decomposition products



No. 1907/2006 (REACH) Printed 11.12.201

revision 01.12.2015 (GB) Version 8.2

RIEGLER Rust remover and contact spray / 400 ml

### Thermal decomposition

Remark No decomposition if used as directed.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

# Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	rat		Naphtha
LD50 acute dermal	> 3000 mg/kg	rabbit		Naphtha
LC50 acute inhalation	5,53 mg/l (4 h)	rat		Informations concern to main component.
Skin irritation	non-irritant			
Eye irritation	non-irritant			
Skin sensitization	non-sensitizing			

### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

### **Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LL0 1000 mg/l (96 h)	Oncorhynchus mykiss		Naphtha
Daphnia	EL0 1000 mg/l (48 h)	Daphnia magna		Naphtha
Algae	EL0 1000 mg/l (72 h)	Pseudokirchneriella subcapitata		Naphtha

### 12.2. Persistence and degradability

No information available.

# 12.3. Bioaccumulative potential

No information available.

# 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

#### **General regulation**

Harmful to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.



No. 1907/2006 (REACH) Printed 11.12.2015

revision 01.12.2015 (GB) Version 8.2

RIEGLER Rust remover and contact spray / 400 ml

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

Product is not allowed to be discharged into aquatic environment.

Harmfull to fishes and bacteria.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste code No.

Name of waste

15 01 10\*

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

#### **General information**

For proper waste disposal a complete emptying of the tin is necessary.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

# 14.6. Special precautions for user

Caution: Gases

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

#### Land and inland navigation transport ADR/RID

Hazard label(s) 2.1 tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

VOC content 25 % VOC value 202 g/L



No. 1907/2006 (REACH)
Printed 11.12.2015

revision 01.12.2015 (GB) Version 8.2

RIEGLER Rust remover and contact spray / 400 ml

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

#### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Danish MAL Code 5-3

H220	Extremely flammable gas.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.