

Karakteristike

| | |
|---------------------------|---|
| Priključak 1 | BSP vanjski navoj, konusni |
| Oblik brtve 1 | brtvljenje navoja |
| Priključak 2 + 3 | metrički vanjski navoji, cilindrični |
| Oblik brtve 2 + 3 | 24° unutarnji konus |
| Izvedba | Uvrtni vijčani spoj |
| Oblik izrade | T oblik |
| Norma | DIN 2353 ISO 8434-1 |
| Opseg isporuke | Nastavak s pretornom maticom i narezanim prstenom |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Napomena

Upute za montažu, ugradnju, tlačno opterećenje i dopuštene radne temperature pronaći ćete u tehničkim informacijama za vijčane spojeve cijevi.

Artikli

| Naziv | Seriya | Radni tlak bari | Vanjski Ø cijevi (mm) | G | i (mm) | L3 (mm) | L4 (mm) | L5 (mm) | SW (mm) | S3 |
|-------------|--------|-----------------|-----------------------|----------|--------|---------|---------|---------|---------|----|
| TR 04 LL | LL | PN 100 | 4 | R 1/8" K | 8 | 21 | 11,0 | 17 | 9 | 10 |
| TR 05 LL | LL | PN 100 | 5 | R 1/8" K | 8 | 21 | 9,5 | 17 | 11 | 12 |
| TR 06 LL | LL | PN 100 | 6 | R 1/8" K | 8 | 21 | 9,5 | 17 | 9 | 12 |
| TR 08 LL | LL | PN 100 | 8 | R 1/8" K | 8 | 23 | 11,5 | 20 | 12 | 14 |
| TR 10 LL | LL | PN 100 | 10 | R 1/4" K | 12 | 24 | 12,5 | 11 | 14 | 17 |
| TR 12 LL | LL | PN 100 | 12 | R 1/4" K | 12 | 25 | 13,0 | 11 | 17 | 19 |
| TR NW 04 HL | L | PN 315 | 6 | R 1/8" K | 8 | 27 | 12,0 | 20 | 12 | 14 |
| TR NW 06 HL | L | PN 315 | 8 | R 1/4" K | 12 | 29 | 14,0 | 26 | 12 | 17 |
| TR NW 08 HL | L | PN 315 | 10 | R 1/4" K | 12 | 30 | 15,0 | 27 | 14 | 19 |
| TR NW 10 HL | L | PN 315 | 12 | R 3/8" K | 12 | 32 | 17,0 | 28 | 17 | 22 |
| TR NW 13 HL | L | PN 315 | 15 | R 1/2" K | 14 | 36 | 21,0 | 34 | 19 | 27 |
| TR NW 16 HL | L | PN 315 | 18 | R 1/2" K | 14 | 40 | 23,5 | 36 | 24 | 32 |
| TR NW 03 HS | S | PN 400 | 6 | R 1/4" K | 12 | 31 | 16,0 | 26 | 12 | 17 |
| TR NW 04 HS | S | PN 400 | 8 | R 1/4" K | 12 | 32 | 17,0 | 27 | 14 | 19 |
| TR NW 06 HS | S | PN 400 | 10 | R 3/8" K | 12 | 34 | 17,5 | 28 | 17 | 22 |
| TR NW 08 HS | S | PN 400 | 12 | R 3/8" K | 12 | 38 | 21,5 | 28 | 17 | 24 |
| TR NW 10 HS | S | PN 400 | 14 | R 1/2" K | 14 | 40 | 22,0 | 32 | 19 | 27 |
| TR NW 13 HS | S | PN 400 | 16 | R 1/2" K | 14 | 43 | 24,5 | 32 | 24 | 30 |

Ø = vanjski promjer cijevi – Serija: LL = veoma lagan L = lagan S = težak – PN = nazivni tlak PB = maks. radni tlak

Varijante proizvoda

| | |
|---------------|---|
| TRK MG | Uvrtni vijčani spoj, T oblik, Mjed |
| TRK VA | Uvrtni vijčani spoj, T oblik, Oplemenjeni čelik |
| XTRK | Uvrtni vijčani spoj, T oblik, Čelik |