

XTN VA

Uvrtni vijčani spoj, T oblik

HANSA FLEX

Karakteristike

| | |
|-------------------|--|
| Priključak 1 | NPT vanjski navoji |
| Oblik brtve 1 | brtvljenje navoja |
| Priključak 2 + 3 | metrički vanjski navoji, cilindrični |
| Oblik brtve 2 + 3 | 24° unutarnji konus |
| Izvedba | Uvrtni vijčani spoj |
| Oblik izrade | T oblik |
| Norma | DIN 2353 |
| Opseg isporuke | Nastavak (bez preturane matice i nareznog prstena) |
| Materijal | Oplemenjeni čelik |



Napomena

Upute za montažu, ugradnju, tlačno opterećenje i dopuštene radne temperature pronaći ćete u tehničkim informacijama za vijčane spojeve cijevi.

Artikli

| Naziv | Serija | Radni tlak bari | Ø d2 (mm) | G | i (mm) | L4 (mm) | L5 (mm) | L7 (mm) | SW (mm) |
|---------------------|--------|-----------------|-----------|-------------------|--------|---------|---------|---------|---------|
| XTN 06 LL VA | LL | PN 100 | 6 | 1/8" -27 NPT | 8 | 9,5 | 17 | 15 | 9 |
| XTN 08 LL VA | LL | PN 100 | 8 | 1/8" -27 NPT | 8 | 11,5 | 20 | 17 | 12 |
| XTN NW 04 HL VA | L | PN 315 | 6 | 1/8" -27 NPT | 8 | 12,0 | 20 | 19 | 12 |
| XTN NW 04 HL 1/4 VA | L | PN 315 | 6 | 1/4" - 18 NPT | 12 | 12,0 | 25 | 19 | 12 |
| XTN NW 06 HL VA | L | PN 315 | 8 | 1/4" - 18 NPT | 12 | 14,0 | 26 | 21 | 12 |
| XTN NW 08 HL VA | L | PN 315 | 10 | 1/4" - 18 NPT | 12 | 15,0 | 27 | 22 | 14 |
| XTN NW 08 HL 3/8 VA | L | PN 315 | 10 | 3/8" - 18 NPT | 15 | 15,0 | 27 | 22 | 14 |
| XTN NW 08 HL 1/2 VA | L | PN 315 | 10 | 1/2" - 14 NPT | 20 | 21,0 | 33 | 29 | 17 |
| XTN NW 10 HL 1/4 VA | L | PN 315 | 12 | 1/4" - 18 NPT | 15 | 17,0 | 28 | 24 | 17 |
| XTN NW 10 HL VA | L | PN 315 | 12 | 3/8" - 18 NPT | 12 | 17,0 | 28 | 24 | 17 |
| XTN NW 10 HL 1/2 VA | L | PN 315 | 12 | 1/2" - 14 NPT | 20 | 21,0 | 34 | 26 | 17 |
| XTN NW 13 HL VA | L | PN 315 | 15 | 1/2" - 14 NPT | 14 | 21,0 | 34 | 26 | 19 |
| XTN NW 16 HL VA | L | PN 315 | 18 | 1/2" - 14 NPT | 14 | 23,5 | 36 | 31 | 24 |
| XTN NW 20 HL VA | L | PN 160 | 22 | 3/4" - 14 NPT | 16 | 27,5 | 42 | 35 | 27 |
| XTN NW 25 HL VA | L | PN 160 | 28 | 1" -11,5 NPT | 18 | 30,5 | 48 | 38 | 36 |
| XTN NW 32 HL VA | L | PN 160 | 35 | 1,1/4" - 11,5 NPT | 20 | 34,5 | 54 | 45 | 41 |
| XTN NW 40 HL VA | L | PN 160 | 42 | 1,1/2" - 11,5 NPT | 22 | 40,0 | 61 | 51 | 50 |
| XTN NW 03 HS VA | S | PN 630 | 6 | 1/4" - 18 NPT | 12 | 16,0 | 26 | 23 | 12 |
| XTN NW 04 HS VA | S | PN 630 | 8 | 1/4" - 18 NPT | 12 | 17,0 | 27 | 24 | 14 |
| XTN NW 06 HS VA | S | PN 630 | 10 | 3/8" - 18 NPT | 12 | 17,5 | 28 | 35 | 17 |
| XTN NW 08 HS VA | S | PN 630 | 12 | 3/8" - 18 NPT | 12 | 21,5 | 31 | 30 | 17 |
| XTN NW 08 HS 1/2 VA | S | PN 630 | 12 | 1/2" - 14 NPT | 20 | 21,5 | 34 | 31 | 19 |
| XTN NW 10 HS VA | S | PN 630 | 14 | 1/2" - 14 NPT | 14 | 22,0 | 32 | 30 | 19 |
| XTN NW 13 HS VA | S | PN 400 | 16 | 1/2" - 14 NPT | 14 | 24,5 | 32 | 33 | 24 |
| XTN NW 16 HS VA | S | PN 400 | 20 | 3/4" - 14 NPT | 16 | 26,5 | 42 | 37 | 27 |
| XTN NW 20 HS VA | S | PN 400 | 25 | 1" -11,5 NPT | 18 | 30,0 | 48 | 42 | 36 |
| XTN NW 25 HS VA | S | PN 400 | 30 | 1,1/4" - 11,5 NPT | 20 | 35,5 | 54 | 49 | 41 |
| XTN NW 32 HS VA | S | PN 315 | 38 | 1,1/2" - 11,5 NPT | 22 | 41,0 | 61 | 57 | 50 |

Serija: LL = veoma lagan L = lagan S = težak - PN = nazivni tlak PB = maks. radni tlak - Ø = vanjski promjer cijevi

Varijante proizvoda

| | |
|-------|---|
| XTN | Uvrtni vijčani spoj, T oblik, Čelik |
| TN VA | Uvrtni vijčani spoj, T oblik, Oplemenjeni čelik |