


Karakteristike

| | |
|---------------------------|---|
| Priključak 1 | metrički unutarnji navoj, cilindrični |
| Oblik brtve 1 | Profil A |
| Priključak 2 | metrički vanjski navoji, cilindrični |
| Oblik brtve 2 | 24° unutarnji konus |
| Izvedba | Navrtni vijčani spoj |
| Oblik izrade | ravno |
| Norma | DIN 2353 ISO 8434-1 |
| Opseg isporuke | Nastavak (bez pretorne matice i nareznog prstena) |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Napomena

Upute za montažu, ugradnju, tlačno opterećenje i dopuštene radne temperature pronaći ćete u tehničkim informacijama za vijčane spojeve cijevi.

Artikli

| Naziv | Seriya | Radni tlak bari | Ø d2 (mm) | G1 | G2 | i (mm) | L1 (mm) | L2 (mm) | SW (mm) |
|------------------|--------|-----------------|-----------|------------|------------|--------|---------|---------|---------|
| XGAM NW 04 HL | L | PN 315 | 6 | M 10 x 1 | M 12 x 1,5 | 12,5 | 26,5 | 19,5 | 14 |
| XGAM NW 04 HL 22 | L | PN 315 | 6 | M 22 x 1,5 | M 12 x 1,5 | 19,0 | 35,0 | 28,0 | 27 |
| XGAM NW 06 HL | L | PN 315 | 8 | M 12 x 1,5 | M 14 x 1,5 | 17,0 | 31,0 | 24,0 | 17 |
| XGAM NW 06 HL 22 | L | PN 315 | 8 | M 22 x 1,5 | M 14 x 1,5 | 19,0 | 35,0 | 29,0 | 27 |
| XGAM NW 08 HL | L | PN 315 | 10 | M 14 x 1,5 | M 16 x 1,5 | 17,0 | 32,0 | 25,0 | 19 |
| XGAM NW 08 HL 22 | L | PN 315 | 10 | M 22 x 1,5 | M 16 x 1,5 | 19,0 | 36,0 | 29,0 | 27 |
| XGAM NW 10 HL | L | PN 315 | 12 | M 16 x 1,5 | M 18 x 1,5 | 17,0 | 33,0 | 26,0 | 22 |
| XGAM NW 10 HL 18 | L | PN 315 | 12 | M 18 x 1,5 | M 18 x 1,5 | 17,0 | 34,0 | 27,0 | 24 |
| XGAM NW 10 HL 22 | L | PN 315 | 12 | M 22 x 1,5 | M 18 x 1,5 | 19,0 | 36,0 | 29,0 | 27 |
| XGAM NW 13 HL | L | PN 315 | 15 | M 18 x 1,5 | M 22 x 1,5 | 17,0 | 35,0 | 28,0 | 24 |
| XGAM NW 13 HL 22 | L | PN 315 | 15 | M 22 x 1,5 | M 22 x 1,5 | 19,0 | 37,0 | 30,0 | 27 |
| XGAM NW 16 HL | L | PN 315 | 18 | M 22 x 1,5 | M 26 x 1,5 | 19,0 | 37,0 | 29,5 | 27 |
| XGAM NW 20 HL | L | PN 160 | 22 | M 26 x 1,5 | M 30 x 2 | 21,0 | 42,0 | 34,5 | 32 |
| XGAM NW 25 HL | L | PN 160 | 28 | M 33 x 2 | M 36 x 2 | 24,0 | 45,0 | 37,5 | 41 |
| XGAM NW 32 HL | L | PN 160 | 35 | M 42 x 2 | M 45 x 2 | 26,0 | 51,0 | 40,5 | 55 |
| XGAM NW 40 HL | L | PN 160 | 42 | M 48 x 2 | M 52 x 2 | 28,0 | 53,0 | 42,0 | 60 |
| XGAM NW 03 HS | S | PN 400 | 6 | M 12 x 1,5 | M 14 x 1,5 | 17,0 | 33,0 | 26,0 | 17 |
| XGAM NW 04 HS | S | PN 400 | 8 | M 14 x 1,5 | M 16 x 1,5 | 17,0 | 33,0 | 26,0 | 19 |
| XGAM NW 06 HS | S | PN 400 | 10 | M 16 x 1,5 | M 18 x 1,5 | 17,0 | 34,0 | 26,5 | 22 |
| XGAM NW 08 HS | S | PN 400 | 12 | M 18 x 1,5 | M 20 x 1,5 | 17,0 | 35,0 | 27,5 | 24 |
| XGAM NW 10 HS | S | PN 400 | 14 | M 20 x 1,5 | M 22 x 1,5 | 19,0 | 39,0 | 31,0 | 27 |
| XGAM NW 13 HS | S | PN 400 | 16 | M 22 x 1,5 | M 24 x 1,5 | 19,0 | 39,0 | 30,5 | 30 |
| XGAM NW 16 HS | S | PN 315 | 20 | M 27 x 2 | M 30 x 2 | 22,0 | 45,0 | 34,5 | 36 |
| XGAM NW 20 HS | S | PN 315 | 25 | M 33 x 2 | M 36 x 2 | 24,0 | 49,0 | 37,0 | 41 |
| XGAM NW 25 HS | S | PN 315 | 30 | M 42 x 2 | M 42 x 2 | 26,0 | 55,0 | 41,5 | 55 |
| XGAM NW 32 HS | S | PN 250 | 38 | M 48 x 2 | M 52 x 2 | 28,0 | 59,0 | 43,0 | 60 |

Seriya: LL = veoma lagan L = lagan S = težak – PN = nazivni tlak PB = maks. radni tlak – Ø d2 = vanjski promjer cijevi

Varijante proizvoda

| | |
|----------------|---|
| XGAM VA | Navrtni vijčani spoj, Oplemenjeni čelik |
| GAM | Navrtni vijčani spoj, Čelik |