

# SW HB

Nastavak pregradnog vijčanog spoja, kut 90°

**HANSA FLEX**

## Karakteristike

<b>Priključak 1</b>	BSP vanjski navoj, cilindrični
<b>Oblik brtve 1</b>	60° unutarnji konus
<b>Priključak 2</b>	BSP vanjski navoj, cilindrični
<b>Oblik brtve 2</b>	60° unutarnji konus
<b>Izvedba</b>	Nastavak pregradnog vijčanog spoja
<b>Oblik izrade</b>	Kutevi 90°
<b>Materijal</b>	Čelik
<b>Površinska zaštita</b>	galvanski premaz



## Artikli

Naziv	G1 + G2	SW (mm)	S1
<b>SW HB 02</b>	G 1/8" - 28	11	14
<b>SW HB 04</b>	G 1/4" - 19	14	19
<b>SW HB 06</b>	G 3/8" - 19	19	22
<b>SW HB 08</b>	G 1/2" - 14	22	27
<b>SW HB 10</b>	G 5/8" - 14	22	30
<b>SW HB 12</b>	G 3/4" - 14	27	32
<b>SW HB 16</b>	G 1" - 11	33	41
<b>SW HB 20</b>	G 1,1/4" - 11	41	50
<b>SW HB 24</b>	G 1,1/2" - 11	50	55

SW, S1, S2 = širina kijuča