

# VERSCHLUSS HB

Čep s nastavkom

**HANSA FLEX**

## Karakteristike

|                    |                                |
|--------------------|--------------------------------|
| Priključak 1       | BSP vanjski navoj, cilindrični |
| Oblik brtve 1      | 60° unutarnji konus            |
| Izvedba            | Čep s nastavkom                |
| Oblik izrade       | ravno                          |
| Materijal          | Čelik                          |
| Površinska zaštita | galvanski premaz               |



## Artikli

| Naziv            | G1            | SW<br>(mm) |
|------------------|---------------|------------|
| VERSCHLUSS HB 02 | G 1/8" - 28   | 14         |
| VERSCHLUSS HB 04 | G 1/4" - 19   | 19         |
| VERSCHLUSS HB 06 | G 3/8" - 19   | 22         |
| VERSCHLUSS HB 08 | G 1/2" - 14   | 27         |
| VERSCHLUSS HB 10 | G 5/8" - 14   | 30         |
| VERSCHLUSS HB 12 | G 3/4" - 14   | 32         |
| VERSCHLUSS HB 16 | G 1" - 11     | 41         |
| VERSCHLUSS HB 20 | G 1,1/4" - 11 | 50         |
| VERSCHLUSS HB 24 | G 1,1/2" - 11 | 55         |
| VERSCHLUSS HB 32 | G 2" - 11     | 70         |

SW, S1, S2 = širina klučca

## Varijante proizvoda

VERSCHLUSS HB VA Čep s nastavkom, Oplemenjeni čelik