

W45 HRO HJ

Uvrtni nastavak, kut 45°

Karakteristike

| | |
|--------------------|------------------------------------|
| Priključak 1 | BSP vanjski navoj, cilindrični |
| Oblik brtve 1 | G oblik |
| Priključak 2 | UN/UNF vanjski navoji |
| Oblik brtve 2 | 74° vanjski konus |
| Izvedba | Uvrtni nastavak, podesiv po smjeru |
| Oblik izrade | Kutevi 45° |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Artikli

| Naziv | G1 | G2 | SW (mm) | S1 | OR |
|------------------|---------------|----------------|------------|----|--------------|
| W45 HRO 02 HJ 05 | G 1/8" - 28 | 1/2" -20 UNF | 13 | 14 | 8,00 x 2,00 |
| W45 HRO 04 HJ | G 1/4" - 19 | 7/16" -20 UNF | 14 | 19 | 10,77 x 2,62 |
| W45 HRO 04 HJ 05 | G 1/4" - 19 | 1/2" -20 UNF | 14 | 19 | 10,77 x 2,62 |
| W45 HRO 04 HJ 08 | G 1/4" - 19 | 3/4" - 16 UNF | 19 | 19 | 10,77 x 2,62 |
| W45 HRO 06 HJ 04 | G 3/8" - 19 | 7/16" -20 UNF | 19 | 22 | 13,94 x 2,62 |
| W45 HRO 06 HJ 05 | G 3/8" - 19 | 1/2" -20 UNF | 19 | 22 | 13,94 x 2,62 |
| W45 HRO 06 HJ | G 3/8" - 19 | 9/16" - 18 UNF | 19 | 22 | 13,94 x 2,62 |
| W45 HRO 06 HJ 10 | G 3/8" - 19 | 7/8" - 14 UNF | 22 | 22 | 13,94 x 2,62 |
| W45 HRO 08 HJ 04 | G 1/2" -14 | 7/16" -20 UNF | 22 | 27 | 17,86 x 2,62 |
| W45 HRO 08 HJ 06 | G 1/2" -14 | 9/16" - 18 UNF | 22 | 27 | 17,86 x 2,62 |
| W45 HRO 08 HJ | G 1/2" -14 | 3/4" - 16 UNF | 22 | 27 | 17,86 x 2,62 |
| W45 HRO 08 HJ 12 | G 1/2" -14 | 1.1/16" -12 UN | 27 | 27 | 17,86 x 2,62 |
| W45 HRO 12 HJ 08 | G 3/4" -14 | 3/4" - 16 UNF | 27 | 36 | 23,47 x 2,62 |
| W45 HRO 12 HJ 10 | G 3/4" -14 | 7/8" - 14 UNF | 27 | 36 | 23,47 x 2,62 |
| W45 HRO 24 HJ | G 1,1/2" - 11 | 1,7/8" -12 UN | 48 | 55 | 44,04 x 3,53 |

SW, S1, S2 = širina ključa