

# W45 O AN

## Uvrtni nastavak, kut 45°

### Karakteristike

<b>Priključak 1</b>	UN/UNF vanjski navoji
<b>Oblik brtve 1</b>	O prstenasta brtva na uvrtnom nastavku
<b>Priključak 2</b>	NPSM navoji matice
<b>Oblik brtve 2</b>	60° vanjski konus
<b>Izvedba</b>	Uvrtni nastavak, podesiv po smjeru
<b>Oblik izrade</b>	Kutevi 45°
<b>Materijal</b>	Čelik
<b>Površinska zaštita</b>	galvanski premaz



### Artikli

Naziv	G1	G2	SW (mm)	S1	S2	OR
<b>W45 O 04 AN</b>	7/16" -20 UNF	1/4" - 18 NPT	11	14	18	8,92 x 1,83
<b>W45 O 06 AN 04</b>	9/16" - 18 UNF	1/4" - 18 NPT	14	22	14	11,90 x 1,98
<b>W45 O 06 AN</b>	9/16" - 18 UNF	3/8" - 18 NPT	14	18	22	11,90 x 1,98
<b>W45 O 08 AN 06</b>	3/4" - 16 UNF	3/8" - 18 NPT	19	22	22	16,36 x 2,20
<b>W45 O 08 AN</b>	3/4" - 16 UNF	1/2" - 14 NPT	19	22	25	16,36 x 2,20
<b>W45 O 08 AN 12</b>	3/4" - 16 UNF	3/4" - 14 NPT	19	22	32	16,36 x 2,20
<b>W45 O 10 AN 08</b>	7/8" -14 UNF	1/2" - 14 NPT	22	25	25	19,18 x 2,46
<b>W45 O 12 AN</b>	1.1/16" -12 UN	3/4" - 14 NPT	27	32	32	23,47 x 2,95

SW, S1, S2 = širina klučca