


W90 HB

Spojnicica, kut 90°

HANSA FLEX

Karakteristike

Priključak 1	BSP vanjski navoj, cilindrični
Oblik brtve 1	60° unutarnji konus
Priključak 2	BSP vanjski navoj, cilindrični
Oblik brtve 2	60° unutarnji konus
Izvedba	Spojnice
Oblik izrade	Kutevi 90°
Materijal	Čelik
Površinska zaštita	galvanski premaz



Artikli

Naziv	G1	G2	SW (mm)
W90 HB 02	G 1/8" - 28	G 1/8" - 28	11
W90 HB 04 HB 02	G 1/4" - 19	G 1/8" - 28	14
W90 HB 04	G 1/4" - 19	G 1/4" - 19	14
W90 HB 06 HB 04	G 3/8" - 19	G 1/4" - 19	19
W90 HB 06	G 3/8" - 19	G 3/8" - 19	19
W90 HB 08 HB 06	G 1/2" - 14	G 3/8" - 19	22
W90 HB 08	G 1/2" - 14	G 1/2" - 14	22
W90 HB 10	G 5/8" - 14	G 5/8" - 14	22
W90 HB 12 HB 08	G 3/4" - 14	G 1/2" - 14	27
W90 HB 12	G 3/4" - 14	G 3/4" - 14	27
W90 HB 16 HB 12	G 1" - 11	G 3/4" - 14	33
W90 HB 16	G 1" - 11	G 1" - 11	33
W90 HB 20 HB 16	G 1,1/4" - 11	G 1" - 11	41
W90 HB 20	G 1,1/4" - 11	G 1,1/4" - 11	41
W90 HB 24	G 1,1/2" - 11	G 1,1/2" - 11	50
W90 HB 32	G 2" - 11	G 2" - 11	55

SW = širina ključa

Varijante proizvoda

W90 HB VA Nastavak vijčanog spoja, kut 90°, Oplemenjeni čelik