


# AFG JIC M (3000 / 6000 PSI)

SAE prirubnica s vanjskim navojem

**HANSA FLEX**

## Karakteristike

<b>Norma</b>	SAE J 518 C ISO 6162
<b>Oblik izrade</b>	ravno
<b>Izvedba</b>	SAE prirubnica s vanjskim navojem
<b>Pričvršćenje</b>	vijčani provrt
<b>Opseg isporuke</b>	s kompletom metričkih vijaka i O prstenom
<b>Materijal</b>	S355J2G3 (ST52.3)
<b>Površinska zaštita</b>	crno nauljeno



## Napomena

Navedeni maksimalni radni tlak odnosi se na prirubnicu! Stvarni radni tlak određuje cijev (debljina stijenke) i kvaliteta cijevi!

## Artikli

Naziv	Tlačni niz	PB 10.9 (bar)	Veličina	A	Ø B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	L (mm)	M metr.
<b>AFG 80 JIC 3/4 M</b>	3000 PSI	350	1/2"	UNF 3/4" -16	9,9	38,1	54	17,5	46	52	13	9,0	M 8 x 30
<b>AFG 80 JIC 7/8 M</b>	3000 PSI	350	1/2"	UNF 7/8" - 14	12,3	38,1	54	17,5	46	52	13	9,0	M 8 x 30
<b>AFG 100 JIC 1 1/16 M</b>	3000 PSI	350	3/4"	UNF 1.1/16" - 12	15,5	47,6	65	22,2	50	60	14	11,5	M 10 x 30
<b>AFG 102 JIC 1 5/16 M</b>	3000 PSI	315	1"	UN 1,5/16" -12	21,5	52,4	70	26,2	55	63	16	11,5	M 10 x 30
<b>AFG 104 JIC 1 5/16 M</b>	3000 PSI	250	1.1/4"	UN 1,5/16" -12	21,5	58,7	79	30,2	68	65	14	11,5	M 10 x 30
<b>AFG 104 JIC 1 5/8 M</b>	3000 PSI	250	1.1/4"	UN 1,5/8" -12	27,5	58,7	79	30,2	68	65	14	11,5	M 10 x 30
<b>AFG 106 JIC 1 7/8 M</b>	3000 PSI	200	1.1/2"	UN 1,7/8" -12	33,0	69,9	94	35,7	78	70	16	13,5	M 12 x 35
<b>AFG 401 JIC 3/4 M</b>	6000 PSI	400	1/2"	UNF 3/4" -16	9,9	40,5	56	18,2	48	60	16	9,0	M 8 x 30
<b>AFG 401 JIC 7/8 M</b>	6000 PSI	400	1/2"	UNF 7/8" - 14	12,3	40,5	56	18,2	48	60	16	9,0	M 8 x 30
<b>AFG 402 JIC 1 1/16 M</b>	6000 PSI	400	3/4"	UNF 1.1/16" - 12	15,5	50,8	71	23,8	60	73	19	11,5	M 10 x 35
<b>AFG 403 JIC 1 5/16 M</b>	6000 PSI	400	1"	UN 1,5/16" -12	21,5	57,2	81	27,8	70	82	24	13,0	M 12 x 45
<b>AFG 404 JIC 1 5/16 M</b>	6000 PSI	400	1.1/4"	UN 1,5/16" -12	21,5	66,7	95	31,8	78	92	27	15,0	M 14 x 50
<b>AFG 404 JIC 1 5/8 M</b>	6000 PSI	400	1.1/4"	UN 1,5/8" -12	27,5	66,7	95	31,8	78	92	27	15,0	M 14 x 50
<b>AFG 405 JIC 1 7/8 M</b>	6000 PSI	400	1.1/2"	UN 1,7/8" -12	33,0	79,4	113	36,5	95	96	30	17,5	M 16 x 50

PN = nazivni tlak PB = maks. radni tlak - Serija: LL = veoma lagan L = lagan S = težak - Ø = vanjski promjer cijevi

## Varijante proizvoda

<b>AFG JIC (3000 PSI)</b>	SAE prirubnica s vanjskim navojem, samo prirubnica
<b>AFG JIC U (3000 / 6000 PSI)</b>	SAE prirubnica s vanjskim navojem, s UNC kompletom vijaka i O prstenom