

AFG JIC U (3000 / 6000 PSI)

SAE prirubnica s vanjskim navojem

HANSA FLEX

Karakteristike

| | |
|---------------------------|-------------------------------------|
| Norma | SAE J 518 C ISO 6162 |
| Oblik izrade | ravno |
| Izvedba | SAE prirubnica s vanjskim navojem |
| Pričvršćenje | vijčani provrt |
| Opseg isporuke | s UNC kompletom vijaka i O prstenom |
| Materijal | S355J2G3 (ST52.3) |
| Površinska zaštita | crno nauljeno |



Napomena

Navedeni maksimalni radni tlak odnosi se na prirubnicu! Stvarni radni tlak određuje cijev (debljina stjenke) i kvaliteta cijevi!

Artikli

| Naziv | Tlačni niz | PB 10.9 (bar) | Veličina | A | Ø B (mm) | C (mm) | D (mm) | E (mm) | F (mm) | G (mm) | H (mm) | L (mm) | M unc |
|----------------------|------------|------------------|----------|------------------|-------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|----------------|
| AFG 80 JIC 3/4 U | 3000 PSI | 350 | 1/2" | UNF 3/4" -16 | 9,9 | 38,1 | 54 | 17,5 | 46 | 52 | 13 | 9,0 | 5/16" x 1.1/4" |
| AFG 80 JIC 7/8 U | 3000 PSI | 350 | 1/2" | UNF 7/8" - 14 | 12,3 | 38,1 | 54 | 17,5 | 46 | 52 | 13 | 9,0 | 3/8" x 1.1/4" |
| AFG 100 JIC 1 1/16 U | 3000 PSI | 350 | 3/4" | UNF 1.1/16" - 12 | 15,5 | 47,6 | 65 | 22,2 | 50 | 60 | 14 | 11,5 | 3/8" x 1.1/4" |
| AFG 102 JIC 1 5/16 U | 3000 PSI | 315 | 1" | UN 1,5/16" -12 | 21,5 | 52,4 | 70 | 26,2 | 55 | 63 | 16 | 11,5 | 3/8" x 1.1/4" |
| AFG 104 JIC 1 5/16 U | 3000 PSI | 250 | 1.1/4" | UN 1,5/16" -12 | 21,5 | 58,7 | 79 | 30,2 | 68 | 65 | 14 | 11,5 | 7/16" x 1.1/2" |
| AFG 104 JIC 1 5/8 U | 3000 PSI | 250 | 1.1/4" | UN 1,5/8" -12 | 27,5 | 58,7 | 79 | 30,2 | 68 | 65 | 14 | 11,5 | 7/16" x 1.1/2" |
| AFG 106 JIC 1 7/8 U | 3000 PSI | 200 | 1.1/2" | UN 1,7/8" -12 | 33,0 | 69,9 | 94 | 35,7 | 78 | 70 | 16 | 13,5 | 1/2" x 1.1/2" |
| AFG 401 JIC 3/4 U | 6000 PSI | 400 | 1/2" | UNF 3/4" -16 | 9,9 | 40,5 | 56 | 18,2 | 48 | 60 | 16 | 9,0 | 5/16" x 1.1/4" |
| AFG 401 JIC 7/8 U | 6000 PSI | 400 | 1/2" | UNF 7/8" - 14 | 12,3 | 40,5 | 56 | 18,2 | 48 | 60 | 16 | 9,0 | 5/16" x 1.1/4" |
| AFG 402 JIC 1 1/16 U | 6000 PSI | 400 | 3/4" | UNF 1.1/16" - 12 | 15,5 | 50,8 | 71 | 23,8 | 60 | 73 | 19 | 11,5 | 3/8" x 1.1/2" |
| AFG 403 JIC 1 5/16 U | 6000 PSI | 400 | 1" | UN 1,5/16" -12 | 21,5 | 57,2 | 81 | 27,8 | 70 | 82 | 24 | 13,0 | 7/16" x 1.3/4" |
| AFG 404 JIC 1 5/16 U | 6000 PSI | 400 | 1.1/4" | UN 1,5/16" -12 | 21,5 | 66,7 | 95 | 31,8 | 78 | 92 | 27 | 13,5 | 1/2" x 1.3/4" |
| AFG 404 JIC 1 5/8 U | 6000 PSI | 400 | 1.1/4" | UN 1,5/8" -12 | 27,5 | 66,7 | 95 | 31,8 | 78 | 92 | 27 | 13,5 | 1/2" x 1.3/4" |
| AFG 405 JIC 1 7/8 U | 6000 PSI | 400 | 1.1/2" | UN 1,7/8" -12 | 33,0 | 79,4 | 113 | 36,5 | 95 | 96 | 30 | 17,5 | 5/8" x 2" |

PN = nazivni tlak PB = maks. radni tlak - Serija: LL = veoma lagan L = lagan S = težak - Ø = vanjski promjer cijevi

Varijante proizvoda

| | |
|-----------------------------|--|
| AFG JIC (3000 PSI) | SAE prirubnica s vanjskim navojem, samo prirubnica |
| AFG JIC M (3000 / 6000 PSI) | SAE prirubnica s vanjskim navojem, s kompletom metričkih vijaka i O prstenom |